Product Information VG.30.01

12-10-2024

VatOil LHM Plus

Description

LHM Plus is a special mineral hydraulic system fluid. It is based on high quality base oils with an extremely high viscosity index.This gives LHM Plus the following properties:

- Very low pouring point
- Does not affect oil-proof seal
- Strong foam-inhibiting properties

Application

LHM Plus is suitable for hydro-pneumatic systems of Citroën and all other automotive applications where a LHM-liquid is prescribed. Always check the product recommendation database for the right application.

Specifications

PSA B71 2710
ISO 7308

Typicals

Density at 15 °C, kg/l	0,837
Viscosity -40 °C, mm²/s	1150
Viscosity 40 °C, mm²/s	18,60
Viscosity 100 °C, mm²/s	6,20
Viscosity Index	330
Flash Point COC, °C	125
Pour Point, °C	-50
Acid number, mgKOH/g	0,05
Boiling Point (reflux) , °C	291
Analinepoint, °C	95

Available packagings

50001
1 L bottle

50002
20 L can

50343
60 L drum

50344
200 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

VatOil Dollegoorweg 15 7602 EC Almelo Phone +31 (0)546-818165. Sales +31 (0)546-816184. Fax +31 (0)546-817367. E-mail sales@vatoil.com