

## Product Information VM.10.04

05-07-2025

### VatOil Syntruck Plus 5W-30

#### Description

SynTruck Plus 5W-30 is a modern, fuel economy, synthetic diesel engine oil. It is based on the latest additive technology combined with very special base oils. The product is developed (considering the official instructions) to allow extended oil change intervals of 80.000km to 120.000km. SynTruck Plus 5W-30 properties:

- Powerful detergency
- Very strong dispersion
- Powerful resistance against wear
- Powerful resistance against corrosion and foam
- Prevents 'bore-polishing'

#### Application

SynTruck Plus 5W-30 is suitable for Heavy Duty diesel engines in trucks buses and industrial applications: vehicles operating under the toughest conditions all year round. SynTruck Plus 5W-30 is very suitable for EURO 3 and EURO 4 diesel engines in combination with diesel fuel with a low sulphur content. Always check the product recommendation database for the right application.

#### Specifications

ACEA E4, E7

Mack EO-N

Renault VI RLD-2

Scania LDF-3

Volvo VDS-3

Cummins CES 20077

DAF Extended Drain

Deutz DQC IV-10

DTFR 15B120

MAN M 3277

MB 228.5

MTU Type 3

#### Typicals

Density at 15 °C, kg/l 0,858

Viscosity -30 °C, mPa.s 6330

Viscosity 40 °C, mm²/s 70,80

Viscosity 100 °C, mm²/s 12,00

Viscosity Index 165

Flash Point COC, °C 226

Pour Point, °C -48

Total Base Number, mgKOH/g 15,3

Sulphate Ash, % 1,80

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

**Available packagings**50007  
20 L can50008  
60 L drum50009  
210 L drum