Product Information VM.20.03
07-07-2025

VatOil Syngold LL 5W-30

Description

SynGold LL 5W-30 is a very modern, synthetic universal engine oil. It is formulated with the highest quality synthetic base oils with a high viscosity index and advanced additive systems. SynGold LL 5W-30 properties:

- Enhanced fuel efficiency by smooth lubrication
- Good fluidity at low temperatures
- Suitable for extended oil change intervals in GM engines
- Very strong protection against wear, corrosion and foaming

Application

SynGold LL 5W-30 is suitable for petrol and diesel engines, with and without turbochargers, in cars and vans insofar as they require the following specifications. SynGold LL 5W-30 complies with the latest applicable Opel Long Life specifications and can be used in Ford Zetec engines.

Specifications

API SN/CF
ACEA A3/B4
BMW Longlife-01
MB 229.3/226.5
Renault RN0700
VW 502.00/505.00
GM LL-A-025/LL-B-025

Typicals

Density at 15 °C, kg/l	0,854
Viscosity -30 °C, mPa.s	6030
Viscosity 40 °C, mm²/s	71,60
Viscosity 100 °C, mm²/s	12,15
Viscosity Index	167
Flash Point COC, °C	233
Pour Point, °C	-39
Total Base Number, mgKOH/g	10,8
Acid number, mgKOH/g	2,10
Sulphate Ash, %	1,32

Available packagings

50016	50017	50139	50140	50141
1 L bottle	4 L can	20 L can	60 L drum	210 L drum