

# Product Information VM.20.07 27-04-2024

## VatOil SynTech LL-X 5W-40

#### Description

SynTech LL-X 5W-40 is a premium, high quality synthetic engine oil. It is manufactured with advanced HC-synthetic base oils and the latest generation additive technology to achieve the following properties:

- Excellent lubrication during the total life span of the lubricant
- Helps reduce fuel consumption
- Good fluidity at low temperatures
- Excellent wear protection enhances engine lifetime

## **Application**

SynTech LL-X 5W-40 is a premium engine oil for petrol and diesel engines of cars and vans. Because of its special formula, Long Life use according the relevant OEM specifications is possible. Always check the product recommendation database for the right application.

#### **Specifications**

| ACEA A3/B4       |
|------------------|
| API SN/CF        |
| BMW Longlife-01  |
| Fiat 9.55535-M2  |
| GM LL-B-025      |
| MB 229.3 / 226.5 |
| Porsche A40      |
| PSA B71 2296     |

.

Renault RN0700 / RN0710

VW 502.00 / 505.00

#### **Typicals**

| Density at 15 °C, kg/l     | 0,856 |
|----------------------------|-------|
| Viscosity -30 °C, mPa.s    | 5970  |
| Viscosity 40 °C, mm²/s     | 83,90 |
| Viscosity 100 °C, mm²/s    | 13,90 |
| Viscosity Index            | 173   |
| Flash Point COC, °C        | 230   |
| Pour Point, °C             | -39   |
| Total Base Number, mgKOH/g | 10,8  |
| Sulphate Ash, %            | 1,33  |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



## **Available packagings**













50034 50035 1 L bottle 4 L can

50036 5 L can

50122 20 L can

50037 60 L drum

50038 210 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.