

**Product Information VM.10.05****17-05-2024****VatOil SynTruck UHPD 10W-40****Description**

SynTruck UHPD 10W-40 (Ultra High Performance Diesel) is a synthetic, top quality, fuel economy diesel engine oil. The product is developed (considering the official instructions) to allow extended oil change intervals for trucks driving long distances. Properties:

- Powerful detergency
- Very strong dispersion
- Powerful resistance against wear
- Powerful resistance against corrosion and foam
- Prevents 'bore-polishing'

**Application**

SynTruck UHPD 10W-40 is suitable for Heavy Duty diesel engines in trucks buses and industrial applications: vehicles operating under the toughest conditions all year round. SynTruck UHPD 10W-40 is very suitable for EURO 3 and EURO 4 diesel engines in combination with diesel fuel with a low sulphur content. Always check the product recommendation database for the right application.

**Specifications**

ACEA E4, E7

API CI-4

Mack EO-N

Renault VI RLD-2

Scania LDF-3

Volvo VDS-3

Cummins CES 20078 / 20077

Deutz IV-18

DTFR 15B120

MAN M 3277

MB 228.5

MTU Type 3

**Typicals**

Density at 15 °C, kg/l 0,867

Viscosity -25 °C, mPa.s 5560

Viscosity 40 °C, mm<sup>2</sup>/s 95,50Viscosity 100 °C, mm<sup>2</sup>/s 14,20

Viscosity Index 153

Flash Point COC, °C 238

Pour Point, °C -42

Total Base Number, mgKOH/g 15,3

Sulphate Ash, % 1,60

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

**Available packagings**50047  
20 L can50048  
60 L drum50049  
210 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.