

Product Information VG.20.02

17-05-2025

VatOil A.T.F. Type III

Description

ATF Type III is a modern automatic transmission oil that complies with the most recent GM Dexron III specification. ATF Type III is a semi-synthetic product with specially selected additives to give the product the following properties:

- Extremely low viscosity at low temperatures
- Extremely high and stable viscosity index
- Excellent resistance to oxidation at high temperatures
- Very high resistance to wear, corrosion and foaming
- Specific friction properties
- Does not affect seals and non-ferrous metals

Application

ATF Type III can be used for automatic transmissions, power-steering units, torque converters and other applications, for which a GM Dexron III or any of the following specifications is recommended.

Specifications

Allison C4 / TES-389

Cat TO-2

DTFR 13C100 / 13C140 / 13C170 / 38B100

Ford Mercon / M2C138-CJ / 166-H

GM Dexron IID / IIE / IIIF / IIIG / IIIH / TASA

MAN 339 Typ Z1 / V1 / Z2

MB 236.1 / 236.3 / 236.5 / 236.6

MB 236.7 / 236.9 / 236.10 / 236.93

Voith 55.6335 (G607)

Volvo 97340 / 97341 (AT101)

ZF TE-ML 02F/03D/04D/09/11A/11B/14A/14B/16L/17C

Typicals

| | |
|--------------------------------------|-------|
| Density at 15 °C, kg/l | 0,848 |
| Viscosity 40 °C, mm ² /s | 36,00 |
| Viscosity 100 °C, mm ² /s | 7,30 |
| Viscosity Index | 175 |
| Flash Point COC, °C | 226 |
| Pour Point, °C | -48 |
| Total Base Number, mgKOH/g | 0,9 |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Available packagings50088
1 L bottle50495
4 L can50991
5 L can50089
20 L can50090
60 L drum50128
210 L drum