

# Product Information VM.20.07 01-05-2024

# VatOil SynTech LL-X 5W-40

#### Description

SynTech LL-X 5W-40 is a premium, high quality synthetic engine oil. It is manufactured with advanced HC-synthetic base oils and the latest generation additive technology to achieve the following properties:

- Excellent lubrication during the total life span of the lubricant
- Helps reduce fuel consumption
- Good fluidity at low temperatures
- Excellent wear protection enhances engine lifetime

## Application

SynTech LL-X 5W-40 is a premium engine oil for petrol and diesel engines of cars and vans. Because of its special formula, Long Life use according the relevant OEM specifications is possible. Always check the product recommendation database for the right application.

#### Specifications

ACEA A3/B4
API SN/CF
BMW Longlife-01
Fiat 9.55535-M2
GM LL-B-025
MB 229.3 / 226.5
Porsche A40
PSA B71 2296
Renault RN0700 / RN0710
VW 502.00 / 505.00

### Typicals

Density at 15 °C, kg/l	0,856
Viscosity -30 °C, mPa.s	5970
Viscosity 40 °C, mm²/s	83,90
Viscosity 100 °C, mm²/s	13,90
Viscosity Index	173
Flash Point COC, °C	230
Pour Point, °C	-39
Total Base Number, mgKOH/g	10,8
Sulphate Ash, %	1,33

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



#### Available packagings

50034 1 L bottle

34 50035 ttle 4 L can

50

50036 5 L can

50122 20 L can

50037 60 L drum



210 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.