

## Product Information VM.10.10

03-05-2024

### VatOil UHPD Plus 15W-40

#### Description

UHPD Plus 15W-40 is a high quality, Heavy Duty engine oil with the following properties:

- Very powerful detergency
- Very strong dispersion
- High and stable natural viscosity index
- Low sulphated ash, phosphor and sulphur content (Low-SAPS)
- Powerful resistance against wear

#### Application

UHPD Plus 15W-40 is suitable for EGR heavy diesel engines with or without DPF performing under the toughest operating conditions all year round. UHPD Plus 15W-40 is a 'Low-SAPS' engine oil. Always check the product recommendation database for the right application.

#### Specifications

ACEA E7, E9, E11

API CK-4 / SN

Meets the requirements of

Mack EOS-4.5

Renault VI RLD-3

Volvo VDS-4.5

Cat ECF-3

Cummins CES 20086

Detroit Diesel 93K222

Deutz DQC III-18 LA

DTFR 15C100

Ford WSS M2C171-F1

JASO DH-2

MAN M 3775

MB 228.31

MTU Type 2.1

Allison TES-439

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

### Typicals

Density at 15 °C, kg/l	0,877
Viscosity -20 °C, mPa.s	5400
Viscosity 40 °C, mm²/s	108,00
Viscosity 100 °C, mm²/s	14,30
Viscosity Index	135
Flash Point COC, °C	240
Pour Point, °C	-42
Total Base Number, mgKOH/g	9,7
Sulphate Ash, %	0,99

### Available packagings



50492  
5 L can



50155  
20 L can



50156  
60 L drum



50157  
210 L drum