

Product Information VG.10.08**25-04-2024****VatOil SynTrag TDL 75W-90****Description**

SynTrag TDL 75W-90 is a universal fully synthetic gear oil. It is based on high quality synthetic base oils and special EP-additives to obtain the following properties:

- Excellent resistance against high temperature load
- Very strong resistance against wear, corrosion and foam
- Low pouring point
- Very special 'Extreme Pressure' properties
- Widely usable

Application

SynTrag TDL 75W-90 is suitable for Long Life use if supported by OEM. This product is developed for manual transmissions and hypoid differentials in passenger cars, delivery vans and heavy trucks. SynTrag TDL 75W-90 is a so called 'Total Drive Line' oil and is therefore widely usable. Always check the product recommendation database for the right application.

Specifications

API GL-3 / GL-4 / GL-5 / MT-1

MIL-L-2105D / MIL-PRF-2105E, SAE J2360

Arvin Meritor 076-N

DAF, Iveco

DTFR 12B140

Mack GO-J

MAN 3343 Typ S / 341 Typ E3 / 341 Typ GA1

MAN 341 Typ Z2 / 342 Typ S1

MB 235.8 / 235.9

Scania STO 1:0 / 1:1 G / 2:0 A FS

Volvo 97312

ZF TE-ML 02B / 05A / 07A / 12B / 12L / 12N / 16B

ZF TE-ML 16F / 17B / 19C / 21A

Typicals

Density at 15 °C, kg/l 0,871

Viscosity 40 °C, mm²/s 95,00Viscosity 100 °C, mm²/s 17,70

Viscosity Index 205

Flash Point COC, °C 198

Pour Point, °C -45

Total Base Number, mgKOH/g 1,4

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Available packagings50165
1 L bottle50166
20 L can50167
60 L drum50168
210 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.