

Product Information VG.10.05

17-04-2024

VatOil Syntrag RPC 75W-80

Description

SynTrag RPC 75W-80 is a universal, mineral multigrade lubricating oil with Extreme Pressure properties. The SynTrag RPC 75W-80 properties:

- Very high resistance against wear, corrosion and foam
- Excellent resistance against oxidation
- Low viscosity at low temperatures
- Very good EP-properties
- High and stable viscosity index

Application

SynTrag RPC 75W-80 is suitable for gearboxes for which a good clutch-switch performance is necessary. The product can also be used where the manufacturer prescribes a gear oil with a low viscosity. Always check the product recommendation database for the right application.

Specifications

API GL-4+

MIL-L-2105

PSA B71 2330

Typicals

Density at 15 °C, kg/l	0,848
Viscosity 40 °C, mm ² /s	49,30
Viscosity 100 °C, mm ² /s	9,15
Viscosity Index	170
Flash Point COC, °C	220
Pour Point, °C	-39
Total Base Number, mgKOH/g	8,7
Acid number, mgKOH/g	1,34
Sulphate Ash, %	1,34

Available packagings



50120
1 L bottle



50125
20 L can



50177
60 L drum



50178
210 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.