

Product Information VM.30.02

17-05-2025

VatOil AgriSyn CVT 10W-40

Description

AgriSyn CVT 10W-40 is a premium quality, semi-synthetic STOU (Super Tractor Oil Universal) This multifunctional product has the following properties:

- Powerful dispersion and detergency
- High resistance against wear, corrosion and foam
- Very strong resistance to oxidation
- Excellent 'Extreme Pressure' properties
- High and stable viscosity index

Application

AgriSyn CVT 10W-40 has been specially developed for everyday operating conditions in agriculture. The universal, multifunctional oil is what is known as an STOU: Super Tractor Oil Universal. It is therefore suitable for use as an all-purpose lubricant for: Petrol engines, Diesel engines and turbo diesels, Transmissions, also for wet brakes and Hydraulic systems.

Specifications

API SF/CG-4/GL-4

ACEA E3, MIL-L-2104D

Allison C4

Cat TO-2

Ford M2C159-C / M2C134-D

John Deere J27 / J20C

Massey Ferguson CMS M1145 / M1144

MB 228.1 / 227.1

ZF TE-ML 06B / 07B

Typicals

Density at 15 °C, kg/l	0,869
Viscosity -25 °C, mPa.s	5440
Viscosity 40 °C, mm ² /s	87,60
Viscosity 100 °C, mm ² /s	13,10
Viscosity Index	148
Flash Point COC, °C	242
Pour Point, °C	-39
Total Base Number, mgKOH/g	11,3
Sulphate Ash, %	1,57

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Available packagings50181
20 L can50182
60 L drum50183
210 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.