

## Product Information VG.10.12

20-04-2024

### VatOil SynTrag LS 75W-85

#### Description

SynTrag LS 75W-85 is a premium quality, fully synthetic transmission oil. It is formulated with special additives to obtain the following properties:

- High viscosity index
- Outstanding oxidation stability
- Good 'Extreme Pressure' and anti-wear properties
- Controlled friction and Limited Slip properties
- Outstanding resistance to corrosion
- High resistance to the formation of foam

#### Application

SynTrag LS 75W-85 is specially developed for (limited slip) differentials of Mercedes Benz for which MB prescribes the MB 235.7 specification. Always check the product recommendation database for the right application.

#### Specifications

API GL-5

MB 235.7 (level)

ZF TE-ML 18 (level)

#### Typicals

Density at 15 °C, kg/l	0,870
Viscosity 40 °C, mm <sup>2</sup> /s	81,50
Viscosity 100 °C, mm <sup>2</sup> /s	12,10
Viscosity Index	144
Flash Point COC, °C	190
Pour Point, °C	-51

#### Available packagings



50214  
20 L can



50313  
60 L drum



50314  
200 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.