

## Product Information VM.40.01

23-06-2018

### VatOil 2T Scoot and Bike

#### Description

2T Scoot and Bike is a semi-synthetic, 2-stroke engine oil. Properties:

- Perfect lubrication of all motor parts
- Active detergency, preventing from deposits in the combustion chamber and at the scavenger ports
- Preventing spark plugs from fouling, in this way securing an optimal output of the engine
- Very effective resistance against wear and corrosion
- Very limited formation of smoke
- Self-mixing

#### Application

2T Scoot and Bike is suitable for high speed, aircooled 2-stroke engines under heavy loads. This selfmixing 2-stroke engine oil can also be used for water cooled 2-stroke engines (radiator type cooling systems) and premix. Always check the product recommendation database for the right application.

#### Specifications

API TC

JASO FD

ISO-L-EGD

2-Stroke DFI

#### Typicals

Density at 15 °C, kg/l	0,872
Viscosity 40 °C, mm <sup>2</sup> /s	64,60
Viscosity 100 °C, mm <sup>2</sup> /s	9,50
Viscosity Index	129
Flash Point PM, °C	100
Flash Point COC, °C	116
Pour Point, °C	-24
Total Base Number, mgKOH/g	1,4
Sulphate Ash, %	0,14

#### Available packagings



50236  
1 L bottle



50285  
20 L can



50286  
60 L drum



50287  
200 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.