

Product Information VM.40.20

06-07-2025

VatOil 4T Motorcycle 10W-40

Description

Motorcycle 4T 10W-40 is a new generation semi-synthetic engine oil. A blend of high quality mineral and synthetic base oils combined with special balanced additives result into the following properties:

- Lower fuel consumption
- High and stable viscosity index
- Good cold start properties
- Optimal friction properties
- Very strong protection against wear, corrosion and foaming
- Very good detergency and dispersion

Application

Motorcycle 4T 10W-40 is suitable for 4-stroke motorcycles with wet clutch. It can also be used for dry clutch systems. The product is tested in the field in cooperation with the most important motorcycle producers. Always check the product recommendation database for the right application.

Specifications

API SN

JASO MA2

Typicals

Density at 15 °C, kg/l	0,861
Viscosity -25 °C, mPa.s	4110
Viscosity 40 °C, mm²/s	92,90
Viscosity 100 °C, mm²/s	14,30
Viscosity Index	159
Flash Point COC, °C	234
Pour Point, °C	-36
Total Base Number, mgKOH/g	7,8
Sulphate Ash, %	0,84
Magnesium, mg/kg	640
Molybdenum, mg/kg	30

Available packagings



50237
1 L bottle



50288
20 L can



50289
60 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.