

Product Information VG.20.07

25-04-2024

VatOil SynMat DCT

Description

SynMat DCT is a synthetic transmission oil for dual clutch transmissions. This specially formulated product with superior characteristics has the following properties:

- Excellent oxidation stability
- Very good lubrication properties
- Outstanding resistance to wear
- High resistance against foaming
- Very low pouring point
- Excellent shear stability

Application

SynMat DCT has been specially developed for the new generation of High Tech DSG transmissions as used in a range of VAG models, along with an increasing number of models by other makes. Always consult the VatOil product advisory database for optimal use.

Specifications

BMW DCTF-1 / 1+ / 2 / LT-5

Borg warner

Bugatti Veyron

Chrysler 68044345 EA & GA

DTFR 13C130

Ferrari TF DCT-F3

Fiat 9.55550-HE2 / MZ6

Ford WSS-M2C936-A / M2C218-A1 / M2C200-D2

Hyundai/Kia

MB 236.21 / 236.22 / 236.24 / 236.25 / 239.21

Mitsubishi Dia-Queen SSTF-1

Porsche/ZF FFL-3

PSA 9734 S2

Renault EDC / DC4 / DW5 / DW6

Volvo 1161838 / 1161839 / D1 / D2

VW G 052 182 / 052 529 / 055 529

VW G 052 536 / 055 536

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Typicals

Density at 15 °C, kg/l	0,850
Viscosity 40 °C, mm ² /s	34,00
Viscosity 100 °C, mm ² /s	7,17
Viscosity Index	183
Flash Point COC, °C	201
Pour Point, °C	-48
Acid number, mgKOH/g	1,29

Available packagings



50266
1 L bottle



50207
20 L can



50331
60 L drum



50332
200 L drum