

## Product Information VM.40.04

26-04-2024

### VatOil Scooter 2T

#### Description

Scooter 2T is a 2-stroke engine oil. It is formulated with carefully selected high quality mineral and synthetic base oils and special 2-stroke additives to achieve the following properties:

- Perfect lubrication of all motor parts
- Very good detergency
- Ensures optimal engine performance
- Very effective resistance against wear and corrosion
- Very limited formation of smoke
- Selfmixing

#### Application

Scooter 2T engine oil is suitable for high speed aircooled 2-stroke engines under Heavy Duty load. This selfmixing 2-stroke engine oil may also be used for water cooled 2-stroke engines (radiator type cooling systems). Always check the product recommendation database for the right application.

#### Specifications

API TC

JASO FD

ISO-L-EGD

2-Stroke DFI

#### Typicals

Density at 15 °C, kg/l	0,873
Viscosity 40 °C, mm <sup>2</sup> /s	64,60
Viscosity 100 °C, mm <sup>2</sup> /s	9,50
Viscosity Index	129
Flash Point PM, °C	100
Flash Point COC, °C	116
Pour Point, °C	-24
Total Base Number, mgKOH/g	1,4
Acid number, mgKOH/g	0,50
Sulphate Ash, %	0,14

#### Available packagings



50240  
1 L bottle



50291  
20 L can



50292  
60 L drum



50293  
200 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.