

Product Information VG.30.03

29-04-2024

VatOil ZHM Fluid

Description

ZHM Fluid is a premium quality hydraulic fluid. It is based on advanced high quality base oils and special additives to obtain the following unique properties:

- Very high viscosity index
- Very low pouring point
- Very strong anti-foaming capacity
- Neutral to seal agents

Application

ZHM Fluid is specially developed for level-control systems in Mercedes Benz passenger cars where the MB 343.0 specification is prescribed. Always check the product recommendation database for the right application.

Specifications

VW 52146 (level)

MB 343.0 (level)

Typicals

Density at 15 °C, kg/l	0,860
Viscosity 40 °C, mm ² /s	21,00
Viscosity 100 °C, mm ² /s	5,10
Viscosity Index	186
Flash Point COC, °C	101
Pour Point, °C	-50

Available packagings



50216
20 L can



50345
60 L drum



50346
200 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.