

Product Information VM.20.23

21-04-2019

Super 20W-50

Description

Super 20W-50 is an engine oil formulated with high quality solvent refined base oils and a number of additives. Super 20W-50 properties:

- Strong detergency and dispersion power
- Strong protection against wear, corrosion and foaming
- Optimal lubrication under a wide range of operating temperatures
- Smooth start
- High and stable viscosity index
- Strong resistance against oxidation

Application

Super 20W-50 is suitable for petrol and diesel engines in passenger cars and vans. Recommended for vehicles which operate under normal driving conditions in all seasons. The product helps keep the engine clean and the balanced multigrade properties assist in easy starting capabilities. Always check the product recommendation database for the right application.

Specifications

Performance level

API SG/CD

CCMC G4

Typicals

Density at 15 °C, kg/l	0,885
Viscosity -15 °C, mPa.s	8700
Viscosity 40 °C, mm ² /s	155,00
Viscosity 100 °C, mm ² /s	17,30
Viscosity Index	121
Flash Point COC, °C	238
Pour Point, °C	-24
Total Base Number, mgKOH/g	6,1
Sulphate Ash, %	0,84
Molybdenum, mg/kg	21

Available packagings



50427
4 L can



50452
20 L can



50453
60 L drum



50454
210 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.