**VATOIL** ®
Pure | Quality Driven

# Product Information VM.20.26
## 17-05-2025

## SynTech LL-X 10W-30

### Description

SynTech LL-X 10W-30 is a premium, high quality semi-synthetic engine oil. It is manufactured with advanced HC-synthetic base oils and the latest generation additive technology to achieve the following properties:

- Excellent lubrication during the total life span of the lubricant
- Helps reduce fuel consumption
- Good fluidity at low temperatures
- Excellent wear protection enhances engine lifetime

### Application

SynTech LL-X 10W-30 is developed for petrol, diesel and gas engines in cars and vans with or without turbocharging. It is suitable for direct injected diesel engines (VW DID test). Because of its special formula, Long Life use according the relevant OEM specifications is possible. Service intervals for vehicles with MB AS System (from March 1997 onwards) may go up to 40.000 km depending on the board computer system. Always check the product recommendation database for the right application.

### Specifications

| |
|---|
| ACEA A3/B4 |
| VW 502.00/505.00 |

### Typicals

| | |
|---|---|
| Density at 15 °C, kg/l | 0,861 |
| Viscosity -25 °C, mPa.s | 3850 |
| Viscosity 40 °C, mm²/s | 75,00 |
| Viscosity 100 °C, mm²/s | 12,15 |
| Viscosity Index | 160 |
| Flash Point COC, °C | 230 |
| Pour Point, °C | -39 |
| Total Base Number, mgKOH/g | 10,8 |
| Sulphate Ash, % | 1,32 |

### Available packagings



| 50956 | 50443 | 50442 | 50444 |
|---|---|---|---|
| 5 L can | 20 L can | 60 L drum | 210 L drum |