

Product Information VM.20.25 25-04-2024

SynTech LL-X 5W-30

Description

SynTech LL-X 5W-30 is a premium, high quality synthetic engine oil. It is manufactured with advanced HC-synthetic base oils and the latest generation additive technology to achieve the following properties:

- Excellent lubrication during the total life span of the lubricant
- Helps reduce fuel consumption
- Good fluidity at low temperatures
- Excellent wear protection enhances engine lifetime

Application

SynTech LL-X 5W-30 is developed for petrol, diesel and gas engines in cars and vans with or without turbocharging. It is suitable for direct injected diesel engines (VW DID test). Because of its special formula, Long Life use according the relevant OEM specifications is possible. Service intervals for vehicles with MB AS System (from March 1997 onwards) may go up to 40.000 km depending on the board computer system. Always check the product recommendation database for the right application.

Specifications

API SN/CF
ACEA A3/B4
BMW Longlife-01
MB 229.3/226.5
Renault RN0700
VW 502.00/505.00

Typicals

Density at 15 °C, kg/l	0,857
Viscosity -30 °C, mPa.s	5870
Viscosity 40 °C, mm²/s	72,80
Viscosity 100 °C, mm²/s	12,15
Viscosity Index	162
Flash Point COC, °C	251
Pour Point, °C	-39
Total Base Number, mgKOH/g	10,8
Acid number, mgKOH/g	2,10
Sulphate Ash, %	1,32

Available packagings













1 L bottle

4 L can

50898 5 L can

20 L can

60 L drum

30478 210 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.