

Product Information VG.20.01 08-05-2024

VatOil A.T.F. Type IID

Description

ATF Type IID is an automatic transmission fluid. It is formulated with mineral base oils and a number of selected additives. ATF Type IID has the following properties:

- Very high and stable viscosity index
- Very low pouring point
- Excellent stability against oxidation
- Positive resistance against wear, corrosion and foaming
- Specific friction properties
- Does not affect seals and non-ferrous metals

Application

ATF Type IID is suitable for automatic gear-boxes, power-steering, torque converters and other equipment, for which a GM Dexron IID fluid is required. Always check the product recommendation database for the right application.

Specifications

Allison C4
Cat TO-2
DTFR 13C140
Ford Mercon / M2C138-CJ / 166-H
GM Dexron IID
MAN 339 Typ Z1 / V1
MB 236.6 / 236.7
Voith 55.6335 (G607)
ZF TE-ML 09 / 11A / 14A

Typicals

Density at 15 °C, kg/l	0,859
Viscosity 40 °C, mm²/s	37,30
Viscosity 100 °C, mm²/s	7,50
Viscosity Index	162
Flash Point COC, °C	225
Pour Point, °C	-48
Total Base Number, mgKOH/g	0,9
Sulphate Ash, %	0,18

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



50496

Available packagings

2 50085 1 L bottle

4 L can

50086 20 L can

50179 60 L drum

50087

210 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.