

Product Information VG.20.09

29-04-2024

SynMulti ATF 5+

Description

SynMulti ATF 5+ is a premium oil for automatic transmissions, based on a number of specially selected base oils. It is supplemented with additives to achieve the following properties:

- Extremely smooth gear-changing
- A very low pour point
- Excellent oxidation stability
- Excellent thermal properties
- Good resistance to wear, corrosion and foaming
- Good frictional stability throughout the long service life of the fluid
- Does not affect seals and non-ferrous metals
- Good resistance to vibration
- Good fuel-saving properties thanks to low viscosity
- Red colour

Application

SynMulti ATF 5+ is a synthetic, multi-functional Long Life ATF for modern, electronically-controlled automatic transmissions in cars and vans. This product is also suitable for use in power steering systems. Always check the product advice database for the correct application.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Specifications

Aisin Warner JWS 3309 / JWS 3317
Allison C4 / TES-389 / TES-295
BMW ATF 6 (83 22 2 355 599)
BMW 7045E / 8072B / LA2634 / LT71141
Chrysler / Dodge / Jeep MS 9602, ATF +4, ATF +3
Fiat 9.55550-AV4
DTRF 13C110 / 13C140 / 13C150 / 13C170 / 13C180
GM Dexron IID, Dexron IIE, Dexron IIIG, Dexron IIH
Ford Mercon V / Mercon / WSS-M2C922-A1
GM Dexron II/IID/IIE/IIIG/IIH / TASA
Honda ATF-Z1 (except in CVT)
Hyundai/Kia SP-II/SP-III/RED-1K, Isuzu ATF II/III
Jaguar JLM 20238/20292/21044, JASO M315 Type 1A
Mazda M-III/Type T-IV / JWS 3309
Mercedes MB 236.14, MB 236.12
Mercedes MB 236.91, MB 236.11, MB 236.10
Mitsubishi SP-II, SP-III, ATF-J2
Nissan Matic-D, Matic-J, Matic-K
Subaru ATF HP, Suzuki ATF 3314/3317
Toyota / Lexus T, T-II, T-III, T-IV
Volvo 1161540
VW G 052 162 / 052 990 / 055 025
ZF TE-ML 11A / 11B
ZF TE ML 11A, 11B
ZF ATF 1375.4 (6HP Transmissions)

Typicals

Density at 15 °C, kg/l	0,861
Viscosity -30 °C, mPa.s	2980
Viscosity 40 °C, mm²/s	33,10
Viscosity 100 °C, mm²/s	7,10
Viscosity Index	185
Flash Point COC, °C	200
Pour Point, °C	-54
Total Base Number, mgKOH/g	4,0

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Available packagings50521
1 L bottle50522
20 L can50523
60 L drum50524
210 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.