

Product Information VG.20.10

30-04-2024

SynMulti ATF 7+

Description

SynMulti ATF 7+ is a premium automatic transmission oil. The product is based on specially selected synthetic base oils with a high viscosity index. It is supplemented with additives to achieve the following properties:

- Excellent dispersive properties that keep sludge to a minimum
- A very low pour point
- Excellent thermal properties and oxidation stability
- Good resistance to wear, corrosion and foaming
- Special friction properties
- Does not affect seals and non-ferrous metals
- Extends the service life of the fluid
- Surpasses the properties of Dexron III fluids
- Red colour

Application

SynMulti ATF 7+ is a synthetic, multi-functional ATF with fuel-saving properties. This product has been specially developed for modern, automatic transmissions by various car manufacturers that require a high-grade, low-viscosity ATF with fuel-saving properties. Always check the product advice database for the correct application.

Specifications

Aisin Warner JWS 3324 / AW-1
 Ford Mercon LV, Mercon SP
 GM Dexron VI
 Honda ATF DW-1
 Hyundai / Kia SP-IV, SP-IV M, SP-IV RR, SPH-IV
 Mazda FZ
 Allison C3/C4 / TES-389/468
 BMW ATF 2/3+/6/7 / 7045E/8072B/LA2634/LT71141
 Cat TO-2, Chrysler ATF+/-2/+3
 DTFR 13C100/120/140/150/170/38B100
 Mercedes MB 236.41
 Nissan Matic K, Matic S, Matic W
 Toyota / Lexus ATF WS
 Fiat 9.55550-AV5/AV6
 GM Dexron VI/II/IID/IIE/IIIG/IIIH / TASA
 Tesla ATF9 / EDF2
 Honda ATF 3.0/3.1/DW-1/Z1(except in CVT)
 Hyundai/Kia SP-IV RR/M / JWS 3314/9638
 Mazda M-III/A7
 Mitsubishi SP-II/SP-III/SP-IV/J2/J3/PA/MA1
 Nissan Matic C/D/J/K/P/S/W
 Porsche 3403-M115/T-IV, PSA B71 2340
 Subaru ATF 5AT/HP, Suzuki ATF 3314/3317
 Toyota D-II/D-III/T-III/T-IV/WS
 Tesla Model S/3/X
 VW G 052 025 / 052 055 / 052 162 / 052 990
 VW G 053 001 / 053 025 / 055 005 / 055 025
 VW G 055 162 / 055 540 / 060 162
 ZF 3-/4-/6-/8-/9-speed / TE-ML 05L/09/11A/B/21L

Typicals

Density at 15 °C, kg/l	0,845
Viscosity 40 °C, mm²/s	29,60
Viscosity 100 °C, mm²/s	5,90
Viscosity Index	149
Flash Point COC, °C	212
Pour Point, °C	-48
Total Base Number, mgKOH/g	2,7
Acid number, mgKOH/g	1,10

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Available packagings50525
1 L bottle50526
20 L can50527
60 L drum50528
210 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.