

Product Information VC.10.02

24-08-2025

VatTex MultiCool -38

Description

MultiCool -38 is a universal, silicate-free, organic coolant with a neutral, light-yellow colour. The product is based on monoethylene glycol and softened water. It is supplemented with special, organic additives to achieve the following properties:

- Excellent protection of all metals that are used in modern engines and cooling systems
- Does not affect gaskets and hoses
- Very good resistance to foaming
- Outstanding protection of aluminium cylinder heads

Application

MultiCool -38 can be used throughout the year in the cooling systems of modern petrol and diesel engines. The product should be used undiluted and will then provide protection down to -38 °C. The maximum replacement interval is 3 years. Always check the product advice database for the correct application.

Specifications

DTFR 29D110

Ford WSS-M97B44-D

MB 326.3

Opel/GM 6277M

VW TL-774F

Typicals

Density at 15 °C, kg/l 1,080

Flash Point COC, °C 111

Available packagings



50542
20 L can



50543
60 L drum



50544
210 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.