

Product Information VG.10.21

05-07-2025

SynTrag HD 75W-90

Description

SynTrag HD 75W-90 is a semi-synthetic lubricant oil for mechanical transmissions. It is based upon high-grade, solvent-refined and synthetic base oils, supplemented with special EP additives. The product has the following properties:

- Effective resistance to oxidation
- Good resistance to corrosion and foaming
- Low pour point
- Good EP properties
- Good gear-changing properties at low temperatures
- Fuel saving

Application

SynTrag HD 75W-90 is used in gearboxes and in other transmissions in which oil with extreme pressure protection is required. This transmission oil can be used whenever a lubricant fulfilling the MB 235.11 specification is required. Always check the product advice database for the correct application.

Specifications

API GL-4

DTFR 13B110

MAN 341 Typ E2

MB 235.11 / 235.21

ZF-TE ML 16A/17A/19A/19C

Typicals

Density at 15 °C, kg/l 0,883

Viscosity 40 °C, mm²/s 99,00

Viscosity 100 °C, mm²/s 16,50

Viscosity Index 181

Flash Point COC, °C 182

Pour Point, °C -45

Available packagings



50551
20 L can



50552
60 L drum



50553
210 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.