

## Product Information VI.20.01

18-04-2024

### Slide Tech 68

#### Description

SlideTech 68 is a universal lubricant for machine tools, based on mineral oil. It is supplemented with additives to achieve the following properties:

- Resistant to high pressures and loads
- Very strong adhesion to metals
- Very strong 'anti stick-slip' ability
- Very effective resistance to wear, corrosion and foaming

#### Application

SlideTech 68 can be used as a combined lubricant for both slideways (stick-slip) in machine tools, as well as the associated hydraulic systems and gear transmissions.

#### Specifications

FZG 12

#### Typicals

|                                      |       |
|--------------------------------------|-------|
| Density at 15 °C, kg/l               | 0,888 |
| Viscosity 40 °C, mm <sup>2</sup> /s  | 68,00 |
| Viscosity 100 °C, mm <sup>2</sup> /s | 8,60  |
| Viscosity Index                      | 97    |
| Flash Point COC, °C                  | 225   |
| Pour Point, °C                       | -24   |
| Acid number, mgKOH/g                 | 0,50  |

#### Available packagings



50568  
20 L can



50517  
60 L drum



50569  
210 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.