

Product Information VM.40.06**09-04-2024****Motorcycle 4T M 10W-40****Description**

Motorcycle 4T M 10W-40 is a 4-stroke engine oil. The product provides total protection under regular riding conditions. Motorcycle 4T M 10W-40 is especially suitable for modern motorcycles, scooters and ATVs.

Application

Motorcycle 4T M 10W-40 is specially made for use in all 4-stroke motorcycles, including European models, whether or not fitted with a wet clutch. The product is also suitable for motorcycles with the latest catalyst technologies. Special attention has been paid to achieving maximum friction in the clutch, even under very high oil temperatures, so that gear changing is as quiet as possible when the engine's operating temperature has not yet been reached.

Specifications

API SG

JASO MA

Typicals

Density at 15 °C, kg/l	0,867
Viscosity -25 °C, mPa.s	3200
Viscosity 40 °C, mm ² /s	85,60
Viscosity 100 °C, mm ² /s	14,00
Viscosity Index	168
Flash Point COC, °C	218
Pour Point, °C	-33
Total Base Number, mgKOH/g	7,7
Sulphate Ash, %	0,94

Available packagings50573
60 L drum50574
210 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.