

Product Information VM.20.39**03-05-2024****SynGold LL-III Premium 5W-30****Description**

SynGold LL-III Premium 5W-30 is a fully synthetic, fuel-saving Low SAPS motor oil. Specially selected base oils, in combination with the latest generation of Low SAPS advanced additives, provide the product with the following properties:

- Fuel saving
- Extended oil change intervals
- A smooth cold start
- Longer service life of exhaust-gas post-treatment systems: Low SAPS
- Protective lubricant film at extremely high operating temperatures
- Excellent dispersion and detergency
- Very high resistance to wear, corrosion and foaming

Application

SynGold LL-III Premium 5W-30 is a universal synthetic Low SAPS motor oil. This Long Life motor oil has been specially developed for cars and vans from the VAG group, Mercedes, BMW, and others. SynGold LL-III Premium 5W-30 is suitable for petrol and diesel engines, both with and without Unit Injector technology. Also suitable for extended oil change intervals and cars with a particulate filter. Always consult the advisory database and/or the vehicle manufacturer's lubrication instructions.

Specifications

ACEA C3

API SP

Approved under VW 504.00 / 507.00

MB-Approval 229.51 / 229.52

BMW Longlife-04

Porsche C30

MB 229.31

Opel OV 040 1547 - D30 / G30

Typicals

Density at 15 °C, kg/l 0,855

Viscosity -30 °C, mPa.s 5980

Viscosity 40 °C, mm²/s 69,80Viscosity 100 °C, mm²/s 12,30

Viscosity Index 176

Flash Point COC, °C 224

Pour Point, °C -42

Total Base Number, mgKOH/g 8,3

Sulphate Ash, % 0,75

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Available packagings



50582
1 L bottle



50583
4 L can



50595
20 L can



50596
60 L drum



50597
210 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.