

# Product Information VM.10.19 12-07-2025

# SHPD Plus 20W-50

#### Description

SHPD Plus 20W-50 is a Super High Performance Diesel engine oil. The advanced additive system is designed to keep the engine clean and to prevent wear. This product guarantees a long engine life with maximum performance. Properties:

- Adjusted to the latest EURO 4 Emission standards
- Suitable for extended oil change intervals
- Can safely be used in combination with SCR and EGR (NOT DPF)
- Cleaner emissions, 'Mid-SAPS' oil, suitable for low sulphur fuels

## Application

SHPD Plus 20W-50 is suitable for Heavy Duty, turbocharged diesel engines of trucks, buses, for marine and industrial use. The product is formulated tot meet the long oil change interval recommendations of leading manufacturers. Recommended and approved by many major OEM's. Always check the product recommendation database for the right application.

#### Specifications

ACEA E7
API CI-4 / SL
Cummins CES 20077 / 20078
Deutz DQC III-18
DTFR 15B110
Global DHD-1
MB 228.3

#### Typicals

Density at 15 °C, kg/l	0,890
Viscosity -15 °C, mPa.s	7500
Viscosity 40 °C, mm²/s	156,30
Viscosity 100 °C, mm²/s	17,50
Viscosity Index	123
Flash Point COC, °C	230
Pour Point, °C	-27
Total Base Number, mgKOH/g	11,1
Acid number, mgKOH/g	3,89
Sulphate Ash, %	1,43

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



## Available packagings

2000 a 50618

4 L can





50619 20 L can



50620

60 L drum



210 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.