

Product Information VS.10.01 17-05-2025

Chainsaw Oil Bio

Description

Chainsaw Oil Bio is a chainsaw oil based on fully biodegradable plant-based oil. The product is supplemented with additives to optimise the adhesion power and lubrication properties of the oil. These specially selected additives are broken down in the environment in a short time. Even at higher temperatures, Chainsaw Oil Bio maintains its excellent adhesion to the chain.

Application

Chainsaw Oil Bio has been specially developed to lubricate the cutting chain on a chainsaw so that it will not jam or break. Chainlube Bio has been authorised to carry the 'Blaue Engel' hallmark by the RAL German Institute for Quality Assurance and Certification.

Please note: Chainlube Bio is NOT suitable for lubricating the drive motor.

Specifications

ISO 6743-1 AC

Biodegradability according OECD 301 B >75%

Typicals

| Density at 15 °C, kg/l | 0,922 |
|-------------------------|-------|
| Viscosity 40 °C, mm²/s | 68,00 |
| Viscosity 100 °C, mm²/s | 14,00 |
| Viscosity Index | 220 |
| Flash Point PM, °C | 180 |
| Flash Point COC, °C | 325 |
| Pour Point, °C | -24 |

Available packagings

| 8 | | |
|----------|-----------|------------|
| 50756 | 50729 | 50623 |
| 20 L can | 60 L drum | 210 L drum |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.