

Product Information VM.20.24

13-07-2025

SynTech LL-X 10W-40

Description

SynTech LL-X 10W-40 is a premium, high quality semi-synthetic engine oil. It is manufactured with advanced HC-synthetic base oils and the latest generation additive technology to achieve the following properties:

- Excellent lubrication during the total life span of the lubricant
- Helps reduce fuel consumption
- Good fluidity at low temperatures
- Excellent wear protection enhances engine lifetime

Application

SynTech LL-X 10W-40 is a premium engine oil for petrol and diesel engines of cars and vans. Because of its special formula, Long Life use according the relevant OEM specifications is possible. Always check the product recommendation database for the right application.

Specifications

ACEA A3/B4

API SN/CF

MB 229.1

VW 501.01/505.00

Typicals

Density at 15 °C, kg/l	0,869
Viscosity -25 °C, mPa.s	6200
Viscosity 40 °C, mm²/s	93,90
Viscosity 100 °C, mm²/s	14,20
Viscosity Index	153
Flash Point COC, °C	224
Pour Point, °C	-39
Total Base Number, mgKOH/g	10,4
Sulphate Ash, %	1,31

Available packagings



50648
1 L bottle



50426
4 L can



50624
5 L can



51008
15 L Bag-in-Box



50439
20 L can



50440
60 L drum



50441
210 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.