Product Information VI.60.05

25-04-2024

GearMax CLP 320

Description

GearMax CLP 320 is a premium, industrial transmission oil. The product is based on mineral oil, supplemented with unleaded 'Extreme Pressure' additives. GearMax CLP 320 features the following properties:

- Excellent resistance to high pressures and shock loads
- Effective resistance to high temperatures
- Effective against rust and corrosion
- Outstanding wear resistance
- Excellent resistance to foaming
- A low pour point

Application

GearMax CLP 320 can be used for the lubrication of nearly all types of industrial gear transmissions that are subject to heavy and/or shock loads.

Specifications

AGMA 9005-F16 (AS)
AIST (US Steel) 224
David Brown S1.53.101 E
DIN 51517-3 CLP
ISO 12925-1 Type CKD

Typicals

Density at 15 °C, kg/l	0,899
Viscosity 40 °C, mm²/s	320,00
Viscosity 100 °C, mm²/s	24,00
Viscosity Index	95
Flash Point COC, °C	248
Pour Point, °C	-15
Acid number, mgKOH/g	0,54

Available packagings

50736
20 L can

50737
60 L drum

50738
210 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

VatOil Dollegoorweg 15 7602 EC Almelo Phone +31 (0)546-818165. Sales +31 (0)546-816184. Fax +31 (0)546-817367. E-mail sales@vatoil.com