

Product Information VG.40.30

17-05-2025

Tracfluid HTF 60

Description

Tracfluid HTF 60 is a very high-quality universal hydraulic transmission oil based on high-quality base oils, to which advanced additives have been added to confer the following properties:

- high and stable viscosity index
- very low pour point
- excellent oxidation stability
- high thermal stability
- good EP and anti-wear properties
- favourable friction properties and therefore suitable for systems with wet brakes
- excellent resistance to corrosion and foaming

Application

Tracfluid HTF 60 is a modern universal tractor transmission oil (UTTO) which has been specially developed for heavy-duty hydraulic systems and transmissions of various agricultural and earth-moving machines. Tracfluid HTF 60 is also perfectly suited for use in systems with wet brakes. This oil can also be used in certain continuously variable transmissions (CVT) of agricultural vehicles.

Specifications

API GL-4

Allison C4

Case MS 1210

Cat TO-2

CNH MAT 3540 / 3525

FNHA-2-C-200.00 / 201.00

Ford M2C86-C / M2C134-D

John Deere J20C/D

Massey Ferguson M1141 / M1143 / M1145

Valtra G2-08 / G2-B10

Volvo WB 101 (97303)

ZF TE-ML 03E / 05F / 06K / 17E / 21F

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Typicals

Density at 15 °C, kg/l	0,868
Viscosity -25 °C, mPa.s	6220
Viscosity 40 °C, mm ² /s	59,80
Viscosity 100 °C, mm ² /s	9,58
Viscosity Index	143
Flash Point COC, °C	235
Pour Point, °C	-45
Total Base Number, mgKOH/g	6,4
Sulphate Ash, %	1,49
Brookfield -26°C, mPa.s	6790

Available packagings50768
20 L can50769
60 L drum50770
210 L drum