

## Product Information VG.40.30

02-05-2024

### Tracfluid HTF 60

#### Description

Tracfluid HTF 60 is a very high-quality universal hydraulic transmission oil based on high-quality base oils, to which advanced additives have been added to confer the following properties:

- high and stable viscosity index
- very low pour point
- excellent oxidation stability
- high thermal stability
- good EP and anti-wear properties
- favourable friction properties and therefore suitable for systems with wet brakes
- excellent resistance to corrosion and foaming

#### Application

Tracfluid HTF 60 is a modern universal tractor transmission oil (UTTO) which has been specially developed for heavy-duty hydraulic systems and transmissions of various agricultural and earth-moving machines. Tracfluid HTF 60 is also perfectly suited for use in systems with wet brakes. This oil can also be used in certain continuously variable transmissions (CVT) of agricultural vehicles.

#### Specifications

API GL-4

Allison C4

Cat TO-2

Case MS 1210

CNH MAT 3540 / 3525

FNHA-2-C-200.00 / 201.00

Ford M2C86-C / M2C134-D

John Deere J20C/D

Massey Ferguson M1141 / M1143 / M1145

Valtra G2-08

Volvo WB 101 (97303)

ZF TE-ML 03E / 05F / 06K / 17E / 21F

#### Typicals

Density at 15 °C, kg/l 0,868

Viscosity -25 °C, mPa.s 6220

Viscosity 40 °C, mm<sup>2</sup>/s 59,80

Viscosity 100 °C, mm<sup>2</sup>/s 9,58

Viscosity Index 143

Flash Point COC, °C 235

Pour Point, °C -45

Total Base Number, mgKOH/g 6,4

Sulphate Ash, % 1,49

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

**Available packagings**

50768  
20 L can



50769  
60 L drum



50770  
210 L drum