

Product Information VM.20.33

17-05-2025

VatOil SynGold LSP-R 5W-30

Description

SynGold LSP-R 5W-30 is a fuel saving, synthetic engine oil. The product has the following properties:

- Low-Ash level, extending the lifespan of the cars emission control
- Less friction, fuel economy with lower CO2 emission
- Extreme protection, strong oil film protects the engine against wear and corrosion
- Fluidity at low temperatures, cold start performance

Application

SynGold LSP-R 5W-30 is a fuel economy motor oil recommended for use in petrol and diesel engines of passenger cars and vans with extended oil drain intervals. Due to its Low SAPS additive content this product can be used in vehicles with modern three way catalysts and diesel particle filters. Always check the product recommendation database for the right application.

Specifications

ACEA C3, C4

MB 229.51/226.51

Renault RN0720

Typicals

Density at 15 °C, kg/l	0,854
Viscosity -30 °C, mPa.s	6320
Viscosity 40 °C, mm ² /s	72,80
Viscosity 100 °C, mm ² /s	12,20
Viscosity Index	170
Flash Point COC, °C	216
Pour Point, °C	-39
Total Base Number, mgKOH/g	6,6
Sulphate Ash, %	0,49

Available packagings



50788
1 L bottle



50789
4 L can



50844
20 L can



50845
60 L drum



50846
210 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.