

Product Information VM.20.40 17-05-2025

VatOil SynGold DX ECO 0W-20

Description

SynGold DX ECO 0W-20 is a premium engine oil. This 'Low viscosity' engine oil is formulated with Fuel Economy technology. Advanced HC-synthetic base oils and the latest generation additive technology give SynGold DX ECO 0W-20 the following properties:

- Safe lubrication film at very high temperatures
- Lower fuel consumption
- Very strong protection against wear, corrosion and foaming
- Very good detergency and dispersion power
- Smooth cold start

Application

SynGold DX ECO 0W-20 is a premium fuel economy motor oil recommended for use in petrol engines of passenger cars and vans with extended oil drain intervals. Always check the product recommendation database for the right application.

Specifications

API SQ Resource Conserving

	7.1.1.2.4 (1.000 at 100
	ILSAC GF-7A
	GM dexos 1 Gen 3
	Chrysler MS 6395
	Fiat 9.55535-CR1
	Ford WSS-M2C947-A/B1 / WSS-M2C962-A1
	GM 6094M

Typicals

Density at 15 °C, kg/l	0,848
Viscosity -35 °C, mPa.s	5740
Viscosity 40 °C, mm²/s	44,50
Viscosity 100 °C, mm ² /s	8,40
Viscosity Index	168
Flash Point COC, °C	226
Pour Point, °C	-42
Total Base Number, mgKOH/g	7,4
Sulphate Ash, %	0,78
Noack, %	10,8

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



Available packagings

















50790 50791 1 L bottle 4 L can

50954 5 L can

51000 15 L Bag in Box

20 L can

50824 60 L drum

50825 210 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.