

Product Information VM.20.17

03-05-2024

VatOil ProTech 20W-50

Description

ProTech 20W-50 is a modern multifunctional engine oil. It is formulated with high quality solvent refined base oils and modern additives to obtain the following properties:

- Strong detergency and dispersion power
- Strong resistance against oxidation
- Strong protection against wear
- Strong protection against corrosion and foaming
- High and stable viscosity index
- Low tendency to evaporation

Application

ProTech 20W-50 is suitable for use in petrol-, diesel-, and LPG-engines, with or without turbo-charging, in passenger cars and vans. Always check the product recommendation database for the right application.

Specifications

ACEA A3/B4

API SL/CF

MB 229.1

VW 501.01/505.00

Typicals

Density at 15 °C, kg/l 0,896

Viscosity -15 °C, mPa.s 8190

Viscosity 40 °C, mm²/s 164,00

Viscosity 100 °C, mm²/s 17,60

Viscosity Index 120

Flash Point COC, °C 238

Pour Point, °C -24

Total Base Number, mgKOH/g 10,3

Sulphate Ash, % 1,29

Available packagings



50797
1 L bottle



50798
4 L can



50957
5 L can



50871
20 L can



50872
60 L drum



50873
210 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.