

Product Information VG.10.13 17-05-2025

VatOil Hypoid GL-4/GL-5 75W

Description

Hypoid GL-4/GL-5 75W is a premium quality, fuel economic transmission oil. The product has the following properties:

- Lower fuel consumption
- High viscosity index
- Outstanding oxidation stability
- Excellent protection against wear
- Outstanding resistance to corrosion
- High resistance to the formation of foam

Application

Hypoid GL-4/GL-5 75W is specially developed for manual transmissions of modern cars and vans which require a fuel economic transmission oil. It is also suitable for transmissions with gear shifting problems. Always check the product recommendation database for the right application.

Specifications

API GL-4/GL-5/MT-1

MIL-L-2105D/MIL-PRF-2105E, SAE J2360

ZF TE-ML 02B

Typicals

Density at 15 °C, kg/l	0,866
Viscosity 40 °C, mm²/s	28,70
Viscosity 100 °C, mm²/s	5,19
Viscosity Index	111
Flash Point COC, °C	190
Pour Point, °C	-39
Total Base Number, mgKOH/g	2,1

Available packagings









50805 1 L bottle

50880 20 L can

50881 60 L drum

50882 210 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.