

## Product Information VM.20.57 03-05-2024

# SYNGOLD MSP-R ECO 0W-20

### Description

SynGold MSP-R ECO 0W-20 is a modern, fuel-saving synthetic Mid-SAPS motor oil. These motor oils contribute significantly to achieving low fuel consumption, which is why manufacturers are increasingly prescribing them ex works. Special synthetic base oils, combined with the latest additives, give the product the following properties:

- High level of fuel saving and stable viscosity index
- Effective resistance against shearing
- A very smooth cold start, even at extremely low outdoor temperatures
- Reduced formation of combustion residues
- Extended service life of particulate filters and catalytic converters
- A protective lubricant film at operating temperatures
- Excellent cleaning ability and strong wear and corrosion resistance

#### Application

SynGold MSP-R ECO 0W-20 has been specially developed for modern petrol and diesel engines in cars and vans equipped with a particulate filter and/or catalytic converter. The special Mid-SAPS formula extends the service life of those components. If the manufacturer so requires, extended oil change intervals are possible. Suitable for application in Renault's latest models that require an RN17 FE specification and for all other brands of cars that require an ACEA C5 specification.

#### Specifications

ACEA C5

Renault RN17 FE

#### Typicals

Density at 15 °C, kg/l	0,844
Viscosity -35 °C, mPa.s	4920
Viscosity 40 °C, mm²/s	40,20
Viscosity 100 °C, mm²/s	8,35
Viscosity Index	190
Flash Point COC, °C	216
Pour Point, °C	-48
Total Base Number, mgKOH/g	8,7
Sulphate Ash, %	0,78
Noack, %	11,6

#### Available packagings

				VAT	Vixt
50813	50814	50815	50832	50833	50834
1 L bottle	4 L can	5 L can	20 L can	60 L drum	210 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.