

## Product Information VM.20.29

20-05-2024

### VatOil SynGold LL 0W-40

#### Description

SynGold LL 0W-40 is a fuel saving, fully synthetic engine oil. It is formulated with high quality base oils and enhanced with advanced additive technology to provide the ultimate performance. Properties:

- Reduces formation of sludge and varnish deposits
- Improves oil film strength and breakdown resistance
- Lowers oil evaporation and consumption at extreme conditions
- Good fluidity at low temperatures
- Extended oil change intervals

#### Application

SynGold LL 0W-40 is a superior fully synthetic engine oil for petrol and diesel engines of cars and vans. Because of its special formula, Long Life use according to the relevant OEM specifications is possible. Always check the product recommendation database for the right application.

#### Specifications

ACEA A3/B4

API SN/CF

BMW Longlife-01

Ford WSS-M2C937-A

MB 229.3 / 229.5

Porsche A40

Renault RN0700/RN0710

VW 502.00/505.00

#### Typicals

Density at 15 °C, kg/l 0,845

Viscosity -35 °C, mPa.s 5900

Viscosity 40 °C, mm²/s 76,90

Viscosity 100 °C, mm²/s 13,40

Viscosity Index 180

Flash Point COC, °C 226

Pour Point, °C -48

Total Base Number, mgKOH/g 10,3

Sulphate Ash, % 1,09

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

**Available packagings**



50786  
1 L bottle



50787  
4 L can



50841  
20 L can



50842  
60 L drum



50843  
210 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.