

Product Information VM.20.08 19-05-2024

VatOil SynGold FE-F 5W-30

Description

SynGold FE-F 5W-30 is a premium engine oil. This 'Low viscosity' engine oil is formulated with Fuel Economy technology. Advanced HC-synthetic base oils and the latest generation additive technology give SynGold FE-F 5W-30 the following properties:

- Safe lubrication film at very high temperatures
- Lower fuel consumption
- Very strong protection against wear, corrosion and foaming
- Very good detergency and dispersion power
- Smooth cold start

Application

SynGold FE-F 5W-30 is a premium fuel economy motor oil recommended for use in petrol and diesel engines of passenger cars and vans with extended oil drain intervals. Always check the product recommendation database for the right application.

Specifications

VW VWC 53036

	ACEA A5/B5, A1/B1
	API SL/CF
	Ford WSS-M2C913-D
	Jaguar Land Rover STJLR.03.5003
	Renault RN0700

Typicals

Density at 15 °C, kg/l	0,853
Viscosity -30 °C, mPa.s	3890
Viscosity 40 °C, mm²/s	54,50
Viscosity 100 °C, mm²/s	9,90
Viscosity Index	170
Flash Point COC, °C	220
Pour Point, °C	-39
Total Base Number, mgKOH/g	10,1
Sulphate Ash, %	1,09

Available packagings











50778 1 L bottle

50779 4 L can

50856

20 L can

50857 60 L drum

50858 210 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.