

## Product Information VM.10.01

19-05-2024

### VatOil ProTruck 15W-40

#### Description

ProTruck 15W-40 is a high performance, universal mixed fleet oil. Properties:

- Keeps the engine clean and in good condition
- Optimal lubrication under a wide range of operating temperatures
- Strong oil film protects the engine against wear and corrosion
- Reduced engine wear by stop and go situations
- Prevents 'Black Sludge'

#### Application

ProTruck 15W-40 is suitable for petrol, LPG and especially diesel engines. The product is engineered to provide extra protection to vehicles operating under severe conditions. ProTruck 15W-40 meets the requirements of most petrol and diesel engines (preferred Diesel Engine Oil by Caterpillar), with or without turbo charging, operating all year round under all conditions. Always check the product recommendation database for the right application.

#### Specifications

ACEA E7

API CH-4/SJ

Cat ECF-1-a

Cummins CES 20076/20077

Deutz DQC III-10

MAN M 3275-1

MB 228.1

MTU Type 2

Volvo VDS-2

#### Typicals

Density at 15 °C, kg/l	0,883
Viscosity -20 °C, mPa.s	5960
Viscosity 40 °C, mm²/s	102,00
Viscosity 100 °C, mm²/s	14,30
Viscosity Index	140
Flash Point COC, °C	220
Pour Point, °C	-33
Total Base Number, mgKOH/g	11,1
Sulphate Ash, %	1,43

**Available packagings**



50799  
1 L bottle



50800  
4 L can



50801  
5 L can



50874  
20 L can



50875  
60 L drum



50876  
210 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.