

Product Information VM.10.11

30-04-2024

VatOil ProTruck 20W-50

Description

ProTruck 20W-50 is a high performance, universal mixed fleet oil. The product is engineered to provide extra protection to vehicles operating under the severe service demands of mixed fleets. Selected additives help minimize sludge formation caused by frequent stop-and-go driving conditions, thereby helping to reduce engine wear. Properties:

- Keeps the engine clean and in good condition
- Thermal and Oxidation stable oil film
- Strong oil film protects the engine against wear and corrosion
- Reduced engine wear by stop and go situations
- Prevents 'Black Sludge'

Application

ProTruck 20W-50 is a universal lubricating oil. It meets the requirements of most petrol and diesel engines (preferred Diesel Engine Oil by Caterpillar), with or without turbo charging, under all operating conditions and all year round. Always check the product recommendation database for the right application.

Specifications

ACEA E7

API CH-4/SJ

Deutz DQC III-10

MB 228.1

Typicals

Density at 15 °C, kg/l	0,894
Viscosity -15 °C, mPa.s	7600
Viscosity 40 °C, mm²/s	154,30
Viscosity 100 °C, mm²/s	17,30
Viscosity Index	122
Flash Point COC, °C	226
Pour Point, °C	-30
Total Base Number, mgKOH/g	11,1
Sulphate Ash, %	1,43

Available packagings



50802
1 L bottle



50803
5 L can



50895
18 L can



50877
20 L can



50878
60 L drum



50879
210 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.