

Product Information VG.20.03

19-04-2024

VatOil SynMat 5HP

Description

SynMat 5HP is an advanced synthetic ATF with the following properties:

- Very good lubrication properties, optimal protection
- Neutral to seal agents used, prevents leakage
- Very low pouring point

Application

SynMat 5HP is suitable for automatic transmissions with a continuously slipping lock-up converter. It is often applied in automatic transmissions of a large number of well-known car manufacturers. Always check the product recommendation database for the right application.

Specifications

Allison C4 / TES-389

Cat TO-2

DTRF 13C100 / 13C140 / 13C170

Ford Mercon / M2C138-CJ / 166-H

GM Dexron IID / IIE / IIIF / IIIG / IIIH

MAN 339 Typ Z1 / V1 / Z2 / V2

MB 236.1/236.5/236.6/236.7/236.9/236.10/236.93

Voith 55.6335 / 55.6336

Volvo 97340 / 97341

ZF TE-ML 02F/03D/04D/09/11A/11B/14A/14B/16L/17C

Ford ESD-M2C-186A

Typicals

Density at 15 °C, kg/l	0,849
Viscosity 40 °C, mm ² /s	34,70
Viscosity 100 °C, mm ² /s	7,40
Viscosity Index	188
Flash Point COC, °C	250
Pour Point, °C	-48
Total Base Number, mgKOH/g	0,9

Available packagings



50806
1 L bottle



50886
20 L can



50887
60 L drum



50888
210 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.