

Product Information VW.10.02

07-05-2024

VatOil Brake Fluid Super LV DOT 4

Description

Brake Fluid Super LV DOT 4 is a premium brake fluid, specially developed for the latest generation of car with electronic safety systems. Brake Fluid Super LV DOT 4 features the following properties:

- Extremely low viscosity, even in extremely cold conditions
- High boiling point, both wet and dry
- Does not affect seals
- Provides outstanding protection against corrosion

Application

Brake Fluid Super LV DOT 4 is a modern low-viscosity, synthetic brake fluid of a very high quality. The product is ideally suited for use in modern cars with electronic safety systems such as ABS, ASR, ESP, EBD, BAS and all of its variations. Brake Fluid Super LV DOT 4 can be easily mixed with other DOT 4 brake fluids.

Specifications

| FMVSS 116 DOT 4 |
|----------------------|
| ISO 4925 Class 6 |
| SAE J 1704 |
| BMW QV 34001 |
| DTFR 30B100 |
| Ford WSS-M6C65-A2 |
| GMW 3356 |
| MB 331.0 |
| Toyota |
| VW 501.14 (TL 766-Z) |

Typicals

| Density at 15 °C, kg/l | 1,035 |
|-----------------------------|-------|
| Viscosity -40 °C, mm²/s | 665 |
| Viscosity 40 °C, mm²/s | 6,40 |
| Viscosity 100 °C, mm²/s | 2,20 |
| Flash Point PM, °C | 150 |
| Flash Point COC, °C | 110 |
| Boiling Point (reflux) , °C | 270 |
| Wet Boiling Point, °C | 170 |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



Available packagings



04

50892 50893 20 L can 60 L drum



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.