Product Information VG.20.13

14-05-2024

ATF Type III NC

Description

ATF Type III NC is a modern automatic transmission oil that complies with the most recent GM Dexron III specification. ATF Type III is a semi-synthetic product with specially selected additives to give the product the following properties:

- Extremely low viscosity at low temperatures
- Extremely high and stable viscosity index
- Excellent resistance to oxidation at high temperatures
- Very high resistance to wear, corrosion and foaming
- Specific friction properties
- Does not affect seals and non-ferrous metals

Application

ATF Type III NC can be used for automatic transmissions, power-steering units, torque converters and other applications, for which a GM Dexron III or any of the following specifications is recommended.

Specifications

Allison C4 / TES-389
Cat TO-2
DTFR 13C100 / 13C140 / 13C170
Ford Mercon / M2C138-CJ / 166-H
GM Dexron IID / IIE / IIIF / IIIG / IIIH
MAN 339 Typ Z1 / V1
MB 236.1 / 236.5 / 236.6 / 236.7 / 236.9 / 236.93
Voith 55.6335 (G607)
Volvo 97341
ZF TE-ML 02F/03D/04D/09/11A/11B/14A/17C

Typicals

Density at 15 °C, kg/l	0,851
Viscosity 40 °C, mm²/s	36,70
Viscosity 100 °C, mm²/s	7,50
Viscosity Index	175
Flash Point COC, °C	226
Pour Point, °C	-48

Available packagings

50951
1 L bottle

50931
4 L can

VatOil Dollegoorweg 15 7602 EC Almelo Phone +31 (0)546-818165. Sales +31 (0)546-816184. Fax +31 (0)546-817367. E-mail sales@vatoil.com