

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 18-4-2023 Revision date: 19-6-2024 Supersedes version of: 27-9-2023 Version: 2.2

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture

Trade name : VatOil Syntruck Plus 5W-30

Product code : VM.10.04
Type of product : Lubricants
Product group : Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use, Consumer use

Use of the substance/mixture : Engine oil

#### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

VatOil

Dollegoorweg 15 NL 7602 EC Almelo Netherlands T 0031 (0)546 81 81 65

vib@vatoil.com

## 1.4. Emergency telephone number

Country/Area	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	National Poisons Information Service (Cardiff Centre) University Hospital Llandough	Penlan Road CF64 2XX	0344 892 0111	Only for healthcare professionals

## **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

#### Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

## 2.2. Label elements

## Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH208 - Contains C14-16-18 Alkyl phenol. May produce an allergic reaction.

EUH210 - Safety data sheet available on request.

19-6-2024 (Revision date) EN (English) 1/16

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

## 2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

Component	
Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9), zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate) (93819-94-4), Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1), Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)
Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9), zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate) (93819-94-4), Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1), Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## **SECTION 3: Composition/information on ingredients**

## 3.1. Substances

Not applicable

#### 3.2. Mixtures

Comments

: Highly refined mineral oils and additives.

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), hydrotreated heavy paraffinic (Note L)	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627- 25	25 – 50	Asp. Tox. 1, H304
Dec-1-ene, trimers, hydrogenated	CAS-No.: 157707-86-3 EC-No.: 500-393-3 REACH-no: 01-2119493949- 12	10 – 20	Asp. Tox. 1, H304
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (Note L)	CAS-No.: 72623-87-1 EC-No.: 276-738-4 EC Index-No.: 649-483-00-5 REACH-no: 01-2119474889- 13	2,5 – 10	Asp. Tox. 1, H304
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (Note L)	CAS-No.: 72623-86-0 EC-No.: 276-737-9 EC Index-No.: 649-482-00-X REACH-no: 01-2119474878-	2,5 – 10	Asp. Tox. 1, H304
Distillates (petroleum), solvent-dewaxed light paraffinic substance with a Community workplace exposure limit (Note L)	CAS-No.: 64742-56-9 EC-No.: 265-159-2 EC Index-No.: 649-469-00-9 REACH-no: 01-2119480132-	0,1 – 2,5	Asp. Tox. 1, H304

2/16

19-6-2024 (Revision date) EN (English)
19-6-2024 (Printing date)

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), solvent-dewaxed heavy paraffinic (Note L)	CAS-No.: 64742-65-0 EC-No.: 265-169-7 EC Index-No.: 649-474-00-6 REACH-no: 01-2119471299- 27	0,1 – 2,5	Asp. Tox. 1, H304
Paraffin oils (petroleum), catalytic dewaxed heavy (Note L)	CAS-No.: 64742-70-7 EC-No.: 265-174-4 REACH-no: 01-2119487080- 42	0,1 – 2,5	Asp. Tox. 1, H304
C14-16-18 Alkyl phenol	EC-No.: 931-468-2 REACH-no: 01-2119498288- 19	0,1 – 2,5	Skin Sens. 1B, H317 STOT RE 2, H373
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)	CAS-No.: 93819-94-4 EC-No.: 298-577-9 REACH-no: 01-2119543726- 33	1 – 2,5	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411

Specific concentration limits:			
Name	Product identifier	Specific concentration limits (%)	
C14-16-18 Alkyl phenol	EC-No.: 931-468-2 REACH-no: 01-2119498288- 19	(10 ≤ C < 100) Skin Sens. 1B, H317	
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)	CAS-No.: 93819-94-4 EC-No.: 298-577-9 REACH-no: 01-2119543726- 33	(6,25 ≤ C ≤ 100) Skin Irrit. 2, H315 (10 ≤ C < 12,5) Eye Irrit. 2, H319 (12,5 ≤ C ≤ 100) Eye Dam. 1, H318	

Comments : The highly refined mineral oil contains <3% (w/w) DMSOextract, according to IP346.

Note L:

The harmonised classification as a carcinogen applies unless it can be shown that the substance contains less than 3 % of dimethyl sulphoxide extract as measured by IP 346 ("Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions – Dimethyl sulphoxide extraction refractive index method" Institute of Petroleum, London), in which case a classification in accordance with Title II of this Regulation shall be performed also for that hazard class.

Full text of H- and EUH-statements: see section 16

## **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

First-aid measures general : If you feel unwell, seek medical advice.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water.
First-aid measures after eye contact : Rinse eyes with water as a precaution.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

## 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : No additional information available.

Symptoms/effects after inhalation : Although no appropriate human or animal health effects data are known to exist, this

material is expected to be an inhalation hazard.

Symptoms/effects after skin contact : None under normal conditions. Symptoms/effects after eye contact : None under normal conditions. Symptoms/effects after ingestion : None under normal conditions.

19-6-2024 (Revision date) EN (English) 3/16 19-6-2024 (Printing date)

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Combustible liquid.
Explosion hazard : No direct explosion hazard.

Hazardous decomposition products in case of fire : Toxic fumes may be released. Incomplete combustion releases dangerous carbon

monoxide, carbon dioxide and other toxic gases.

## 5.3. Advice for firefighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper

protective equipment, including respiratory protection.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

## **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters.

Absorb spillage to prevent material damage.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : Ventilate spillage area.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

#### 6.2. Environmental precautions

Avoid release to the environment.

## 6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to

prevent migration and entry into sewers or streams. Stop leak without risks if possible.

Methods for cleaning up : Take up liquid spill into absorbent material.

Other information : Dispose of materials or solid residues at an authorized site.

## 6.4. Reference to other sections

For further information refer to section 13.

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

Precautions for safe handling : Provide good ventilation in process area to prevent formation of vapour.

19-6-2024 (Revision date) EN (English) 4/16

19-6-2024 (Printing date)

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hygiene measures

: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Keep in a cool, well-ventilated place away from heat.

Storage conditions

: Keep container closed when not in use. Keep in a cool, well-ventilated place away from

heat.

Storage temperature

: 0 - 40 °C

Packaging materials

: Store always product in container of same material as original container.

#### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

### VatOil Syntruck Plus 5W-30

## **EU - Indicative Occupational Exposure Limit (IOEL)**

Exposure limits/standards for materials that can be formed when handling this product. When mists/aerosols can occur the following is recommended

5 mg/m3 - ACGIH TLV (inhalable fraction).

## Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)

## **EU - Indicative Occupational Exposure Limit (IOEL)**

IOEL TWA 5 mg/m³

## 8.1.2. Recommended monitoring procedures

No additional information available

#### 8.1.3. Air contaminants formed

No additional information available

## 8.1.4. DNEL and PNEC

No additional information available

#### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

## 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

#### 8.2.2. Personal protection equipment

#### Personal protective equipment:

Wear recommended personal protective equipment.

#### Personal protective equipment symbol(s):







## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### 8.2.2.1. Eye and face protection

#### Eye protection:

Safety glasses

Eye protection			
Туре	Field of application	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166

#### 8.2.2.2. Skin protection

### Skin and body protection:

Wear suitable protective clothing

#### Hand protection:

Protective gloves

Hand protection					
Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Reusable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	≥0.35		EN ISO 374

#### Other skin protection

#### Materials for protective clothing:

Wear suitable protective clothing

## 8.2.2.3. Respiratory protection

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

#### 8.2.2.4. Thermal hazards

No additional information available

#### 8.2.3. Environmental exposure controls

#### **Environmental exposure controls:**

Avoid release to the environment.

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state : Liquid
Colour : brown.
Odour : characteristic.
Odour threshold : Not available
Melting point : Not applicable

Freezing point : -48 °C - ASTM D5950 (pour point)

Boiling point : Not available Flammability : Not applicable

Explosive properties : Presents no particular fire or explosion hazard.

Lower explosion limit : Not available Upper explosion limit : Not available

Flash point : 226 °C - ASTM D92 (COC)

Auto-ignition temperature : Not available
Decomposition temperature : Not available
pH : Not available
it is not available

Viscosity, kinematic : 70,8 mm²/s (40 °C) - ASTM D7042 Solubility : Water: Insoluble / Slightly miscible

Partition coefficient n-octanol/water (Log Kow) : Not available

19-6-2024 (Revision date) EN (English) 6/16 19-6-2024 (Printing date)

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Vapour pressure : Not available Vapour pressure at 50°C : Not available

Density : 0,858 kg/l (15 °C) - ASTM D4052

Relative density : Not available
Relative vapour density at 20°C : Not available
Particle characteristics : Not applicable

#### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

VOC content : 0 %

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

#### 10.2. Chemical stability

Stable under normal conditions.

## 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use. Reacts violently with (strong) oxidizers.

#### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

## 10.5. Incompatible materials

No additional information available

#### 10.6. Hazardous decomposition products

No decomposition if stored normally.

## **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Dec-1-ene, trimers, hydrogenated (157707-86-3)		
LD50 oral rat	> 2000 mg/kg bodyweight	
LD50 dermal	> 2000 mg/kg bodyweight	
Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)		
LD50 oral rat	> 5000 mg/kg	
LD50 dermal rabbit	> 5000 mg/kg	
LC50 Inhalation - Rat (Dust/Mist)	5,53 mg/l/4h	
Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)		
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral	

19-6-2024 (Revision date) EN (English) 7/16

Toxicity), Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Distillates (petroleum), hydrotreated heavy pa	araffinic (64742-54-7)
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat	> 5,53 mg/l/4h
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)	bis(dithiophosphate) (93819-94-4)
LD50 oral rat	2600 mg/kg bodyweight Animal: rat, Animal sex: male, Remarks on results: other:
LD50 dermal rabbit	> 3160 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Remarks on results: other:
LC50 Inhalation - Rat	> 2 mg/l (1h) - OECD403
C14-16-18 Alkyl phenol	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method), Guideline: EU Method B.1 tris (Acute Oral Toxicity - Acute Toxic Class Method), Guideline: EPA OPPTS 870.1100 (Acute Oral Toxicity), Guideline: other:
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal)), Guideline: EPA OPPTS 870.1200 (Acute Dermal Toxicity), Guideline: other:
Lubricating oils (petroleum), C20-50, hydrotre	eated neutral oil-based (72623-87-1)
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)
LD50 dermal rabbit	> 2000 mg/kg (OECD 402 method)
LC50 Inhalation - Rat	5,53 mg/l/4h (OECD 403 method)
Lubricating oils (petroleum), C15-30, hydrotre	eated neutral oil-based (72623-86-0)
LD50 oral rat	> 5000 mg/kg (OECD 401 method)
LD50 dermal rabbit	> 2000 mg/kg (OECD 402 method)
LC50 Inhalation - Rat	> 5,53 mg/l (OECD 403 method)
Skin corrosion/irritation :	Not classified
Serious eye damage/irritation :	Not classified
Respiratory or skin sensitisation :	Not classified
Germ cell mutagenicity :	Not classified
Carcinogenicity :	Not classified
Reproductive toxicity :	Not classified
STOT-single exposure :	Not classified
STOT-repeated exposure  Distillates (petroleum), solvent-dewaxed light	Not classified
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day ≥ 2000 mg/kg bodyweight
NOAEL (subchronic, oral, animal/male, 90 days)	
NOAEL (subchronic, oral, animal/female, 90 days)	≥ 2000 mg/kg bodyweight
Distillates (petroleum), solvent-dewaxed heav	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	≈ 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)

19-6-2024 (Revision date) 19-6-2024 (Printing date)

EN (English)

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

C14-16-18 Alkyl phenol           STOT-repeated exposure         May cause damage to organs (liver) through prolonged or repeated exposure.           Lubricating oils (petroleum), C20-50, hydrottable neutral oil-based (72623-87-1)           LoAEL (oral, rat, 90 days)         125 mg/kg bodywelpht Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)           Aspiration hazard         Not classified           VatCII Syntruck Plus 5W-30           Viscosity, kinematic         70.8 mm/s (40 °C) - ASTM D7042           Distillates (petroleum), solvent-dewaxed light paraffinic (64742-65-9)           Viscosity, kinematic         < 20.5 mm/s			
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)  LOAEL (oral, rat, 90 days)   125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)  Aspiration hazard : Not classified  VatOil Syntruck Plus 5W-30  Viscosity, kinematic   70,8 mm²/s (40 °C) - ASTM D7042  Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)  Viscosity, kinematic   < 20,5 mm²/s  Aliphatic, alicyclic or aromatic hydrocarbon   Yes  Paraffin oils (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)  Viscosity, kinematic   < 20,5 mm²/s (40 °C)   5,4 mm²/s  Aliphatic, alicyclic or aromatic hydrocarbon   Yes  Paraffin oils (petroleum), catalytic dewaxed heavy (64742-70-7)  Viscosity, kinematic   < 20,5 mm²/s  Aliphatic, alicyclic or aromatic hydrocarbon   Yes  Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)  Viscosity, kinematic   < 20,5 mm²/s  Aliphatic, alicyclic or aromatic hydrocarbon   Yes  Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)  Viscosity, kinematic   < 20,5 mm²/s  Aliphatic, alicyclic or aromatic hydrocarbon   Yes  C14-16-18 Alkyl phenol  Viscosity, kinematic   52 mm²/s (40 °C)   5,4 mm³/s (100 °C) (ASTM D445)  Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)  Viscosity, kinematic   < 20,5 mm²/s (40 °C) - ASTM D7042  Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)  Viscosity, kinematic   < 20,5 mm²/s (40 °C) - ASTM D7042	C14-16-18 Alkyl phenol		
LOAEL (oral, rat, 90 days)  125 mg/kg bodywelght Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)  Aspiration hazard : Not classified  VatOil Syntruck Plus 5W-30  Viscosity, kinematic 70,8 mm²/s (40 °C) - ASTM D7042  Distillates (petroleum), solvent-dewaxed light paraffinic (64742-65-9)  Viscosity, kinematic 20,5 mm²/s  Aliphatic, alloyclic or aromatic hydrocarbon Yes  Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)  Viscosity, kinematic 20,5 mm²/s @40°C  Aliphatic, alloyclic or aromatic hydrocarbon Yes  Paraffin oils (petroleum), catalytic dewaxed heavy (64742-70-7)  Viscosity, kinematic 20,5 mm²/s  Aliphatic, alloyclic or aromatic hydrocarbon Yes  Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)  Viscosity, kinematic 20,5 mm²/s  Aliphatic, alloyclic or aromatic hydrocarbon Yes  C14-16-18 Alkyl phenol  Viscosity, kinematic 52 mm²/s (40°C) [5.4 mm²/s (100°C) [ASTM D445]  Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-86-0)  Viscosity, kinematic 20,5 mm²/s (40°C) - ASTM D7042  Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)  Viscosity, kinematic 20,5 mm²/s (40°C) - ASTM D7042	STOT-repeated exposure	May cause damage to organs (liver) through prolonged or repeated exposure.	
Repeated Dose 90-Day Oral Toxicity in Rodents)   Aspiration hazard : Not classified	Lubricating oils (petroleum), C20-50, hydrotre	ated neutral oil-based (72623-87-1)	
Vatoli Syntruck Plus 5W-30  Viscosity, kinematic  70,8 mm²/s (40 °C) - ASTM D7042  Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)  Viscosity, kinematic  Aliphatic, alicyclic or aromatic hydrocarbon  Pes  Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)  Viscosity, kinematic  Aliphatic, alicyclic or aromatic hydrocarbon  Yes  Paraffin oils (petroleum), catalytic dewaxed heavy (64742-70-7)  Viscosity, kinematic  Yes  Aliphatic, alicyclic or aromatic hydrocarbon  Yes  Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)  Viscosity, kinematic  20,5 mm²/s  Aliphatic, alicyclic or aromatic hydrocarbon  Yes  C14-16-18 Alkyl phenol  Viscosity, kinematic  52 mm²/s (40°C)   5,4 mm²/s (100°C) [ASTM D445]  Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)  Viscosity, kinematic  20,5 mm²/s (40°C) - ASTM D7042  Aliphatic, alicyclic or aromatic hydrocarbon  Yes  Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)  Viscosity, kinematic  20,5 mm²/s (40°C) - ASTM D7042	LOAEL (oral, rat, 90 days)		
Viscosity, kinematic  Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)  Viscosity, kinematic  Aliphatic, alicyclic or aromatic hydrocarbon  Ves  Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)  Viscosity, kinematic  < 20,5 mm²/s @40°C  Aliphatic, alicyclic or aromatic hydrocarbon  Yes  Paraffin oils (petroleum), catalytic dewaxed heavy (64742-70-7)  Viscosity, kinematic  < 20,5 mm²/s  Hydrocarbon  Yes  Distillates (petroleum), datalytic dewaxed heavy (64742-70-7)  Viscosity, kinematic  < 20,5 mm²/s  Hydrocarbon  Yes  Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)  Viscosity, kinematic  < 20,5 mm²/s  Aliphatic, alicyclic or aromatic hydrocarbon  Yes  C14-16-18 Alkyl phenol  Viscosity, kinematic  \$2 mm²/s (40°C)   5,4 mm²/s (100°C) [ASTM D445]  Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)  Viscosity, kinematic  < 20,5 mm²/s (40°C) - ASTM D7042  Aliphatic, alicyclic or aromatic hydrocarbon  Yes  Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)  Viscosity, kinematic  < 20,5 mm²/s (40°C) - ASTM D7042	Aspiration hazard :	Not classified	
Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)  Viscosity, kinematic   Aliphatic, alicyclic or aromatic hydrocarbon  Yes  Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)  Viscosity, kinematic   Aliphatic, alicyclic or aromatic hydrocarbon  Yes  Paraffin oils (petroleum), catalytic dewaxed heavy (64742-70-7)  Viscosity, kinematic   420,5 mm²/s  Hydrocarbon  Yes  Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)  Viscosity, kinematic   420,5 mm²/s  Aliphatic, alicyclic or aromatic hydrocarbon  Yes  Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)  Viscosity, kinematic   420,5 mm²/s  Aliphatic, alicyclic or aromatic hydrocarbon  Yes  C14-16-18 Alkyl phenol  Viscosity, kinematic  52 mm²/s (40°C)   5.4 mm²/s (100°C) [ASTM D445]  Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)  Viscosity, kinematic  420,5 mm²/s (40°C) - ASTM D7042  Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)  Viscosity, kinematic  420,5 mm²/s (40°C) - ASTM D7042	VatOil Syntruck Plus 5W-30		
Viscosity, kinematic  < 20,5 mm²/s  Aliphatic, alicyclic or aromatic hydrocarbon  Ves  Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)  Viscosity, kinematic  < 20,5 mm²/s @40°C  Aliphatic, alicyclic or aromatic hydrocarbon  Yes  Paraffin oils (petroleum), catalytic dewaxed heavy (64742-70-7)  Viscosity, kinematic  < 20,5 mm²/s  Hydrocarbon  Yes  Aliphatic, alicyclic or aromatic hydrocarbon  Yes  Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)  Viscosity, kinematic  < 20,5 mm²/s  Aliphatic, alicyclic or aromatic hydrocarbon  Yes  C14-16-18 Alkyl phenol  Viscosity, kinematic  52 mm²/s (40°C)   5.4 mm²/s (100°C) [ASTM D445]  Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)  Viscosity, kinematic  < 20,5 mm²/s (40 °C) - ASTM D7042  Aliphatic, alicyclic or aromatic hydrocarbon  Yes  Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)  Viscosity, kinematic  < 20,5 mm²/s (40 °C) - ASTM D7042	Viscosity, kinematic	70,8 mm²/s (40 °C) - ASTM D7042	
Aliphatic, alicyclic or aromatic hydrocarbon Viscosity, kinematic Aliphatic, alicyclic or aromatic hydrocarbon Viscosity, kinematic Aliphatic, alicyclic or aromatic hydrocarbon Viscosity, kinematic	Distillates (petroleum), solvent-dewaxed light	paraffinic (64742-56-9)	
Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)  Viscosity, kinematic < 20,5 mm²/s @40°C  Aliphatic, alicyclic or aromatic hydrocarbon Yes  Paraffin oils (petroleum), catalytic dewaxed heavy (64742-70-7)  Viscosity, kinematic < 20,5 mm²/s  Hydrocarbon Yes  Aliphatic, alicyclic or aromatic hydrocarbon Yes  Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)  Viscosity, kinematic < 20,5 mm²/s  Aliphatic, alicyclic or aromatic hydrocarbon Yes  C14-16-18 Alkyl phenol  Viscosity, kinematic 52 mm²/s (40°C)   5,4 mm²/s (100°C) [ASTM D445]  Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)  Viscosity, kinematic < 20,5 mm²/s (40°C) - ASTM D7042  Aliphatic, alicyclic or aromatic hydrocarbon Yes  Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)  Viscosity, kinematic < 20,5 mm²/s (40°C) - ASTM D7042	Viscosity, kinematic	< 20,5 mm²/s	
Viscosity, kinematic    Viscosity, kinematic	Aliphatic, alicyclic or aromatic hydrocarbon	Yes	
Aliphatic, alicyclic or aromatic hydrocarbon  Paraffin oils (petroleum), catalytic dewaxed heavy (64742-70-7)  Viscosity, kinematic  < 20,5 mm²/s  Hydrocarbon  Yes  Aliphatic, alicyclic or aromatic hydrocarbon  Pes  Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)  Viscosity, kinematic  < 20,5 mm²/s  Aliphatic, alicyclic or aromatic hydrocarbon  Yes  C14-16-18 Alkyl phenol  Viscosity, kinematic  52 mm²/s (40°C)   5,4 mm²/s (100°C) [ASTM D445]  Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)  Viscosity, kinematic  < 20,5 mm²/s (40°C) - ASTM D7042  Aliphatic, alicyclic or aromatic hydrocarbon  Yes  Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)  Viscosity, kinematic  < 20,5 mm²/s (40°C) - ASTM D7042	Distillates (petroleum), solvent-dewaxed heav	y paraffinic (64742-65-0)	
Paraffin oils (petroleum), catalytic dewaxed heavy (64742-70-7)  Viscosity, kinematic < 20,5 mm²/s  Hydrocarbon Yes  Aliphatic, alicyclic or aromatic hydrocarbon Yes  Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)  Viscosity, kinematic < 20,5 mm²/s  Aliphatic, alicyclic or aromatic hydrocarbon Yes  C14-16-18 Alkyl phenol  Viscosity, kinematic 52 mm²/s (40°C)   5,4 mm²/s (100°C) [ASTM D445]  Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)  Viscosity, kinematic < 20,5 mm²/s (40°C) - ASTM D7042  Aliphatic, alicyclic or aromatic hydrocarbon Yes  Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)  Viscosity, kinematic < 20,5 mm²/s (40°C) - ASTM D7042	Viscosity, kinematic	< 20,5 mm²/s @40°C	
Viscosity, kinematic < 20,5 mm²/s  Hydrocarbon Yes  Aliphatic, alicyclic or aromatic hydrocarbon Yes  Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)  Viscosity, kinematic < 20,5 mm²/s  Aliphatic, alicyclic or aromatic hydrocarbon Yes  C14-16-18 Alkyl phenol  Viscosity, kinematic 52 mm²/s (40°C)   5,4 mm²/s (100°C) [ASTM D445]  Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)  Viscosity, kinematic < 20,5 mm²/s (40 °C) - ASTM D7042  Aliphatic, alicyclic or aromatic hydrocarbon Yes  Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)  Viscosity, kinematic < 20,5 mm²/s (40 °C) - ASTM D7042	Aliphatic, alicyclic or aromatic hydrocarbon	Yes	
Hydrocarbon Yes  Aliphatic, alicyclic or aromatic hydrocarbon Yes  Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)  Viscosity, kinematic < 20,5 mm²/s  Aliphatic, alicyclic or aromatic hydrocarbon Yes  C14-16-18 Alkyl phenol  Viscosity, kinematic 52 mm²/s (40°C)   5,4 mm²/s (100°C) [ASTM D445]  Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)  Viscosity, kinematic < 20,5 mm²/s (40 °C) - ASTM D7042  Aliphatic, alicyclic or aromatic hydrocarbon Yes  Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)  Viscosity, kinematic < 20,5 mm²/s (40 °C) - ASTM D7042	Paraffin oils (petroleum), catalytic dewaxed heavy (64742-70-7)		
Aliphatic, alicyclic or aromatic hydrocarbon  Pes  Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)  Viscosity, kinematic  < 20,5 mm²/s  Aliphatic, alicyclic or aromatic hydrocarbon  Yes  C14-16-18 Alkyl phenol  Viscosity, kinematic  52 mm²/s (40°C)   5,4 mm²/s (100°C) [ASTM D445]  Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)  Viscosity, kinematic  < 20,5 mm²/s (40°C) - ASTM D7042  Aliphatic, alicyclic or aromatic hydrocarbon  Yes  Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)  Viscosity, kinematic  < 20,5 mm²/s (40°C) - ASTM D7042	Viscosity, kinematic	< 20,5 mm²/s	
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)  Viscosity, kinematic < 20,5 mm²/s  Aliphatic, alicyclic or aromatic hydrocarbon Yes  C14-16-18 Alkyl phenol  Viscosity, kinematic 52 mm²/s (40°C)   5,4 mm²/s (100°C) [ASTM D445]  Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)  Viscosity, kinematic < 20,5 mm²/s (40 °C) - ASTM D7042  Aliphatic, alicyclic or aromatic hydrocarbon Yes  Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)  Viscosity, kinematic < 20,5 mm²/s (40 °C) - ASTM D7042	Hydrocarbon	Yes	
Viscosity, kinematic  Aliphatic, alicyclic or aromatic hydrocarbon  Yes  C14-16-18 Alkyl phenol  Viscosity, kinematic  52 mm²/s (40°C)   5,4 mm²/s (100°C) [ASTM D445]  Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)  Viscosity, kinematic  < 20,5 mm²/s (40 °C) - ASTM D7042  Aliphatic, alicyclic or aromatic hydrocarbon  Yes  Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)  Viscosity, kinematic  < 20,5 mm²/s (40 °C) - ASTM D7042	Aliphatic, alicyclic or aromatic hydrocarbon	Yes	
Aliphatic, alicyclic or aromatic hydrocarbon  Yes  C14-16-18 Alkyl phenol  Viscosity, kinematic  52 mm²/s (40 °C)   5,4 mm²/s (100 °C) [ASTM D445]  Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)  Viscosity, kinematic  < 20,5 mm²/s (40 °C) - ASTM D7042  Aliphatic, alicyclic or aromatic hydrocarbon  Yes  Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)  Viscosity, kinematic  < 20,5 mm²/s (40 °C) - ASTM D7042	Distillates (petroleum), hydrotreated heavy pa	raffinic (64742-54-7)	
C14-16-18 Alkyl phenol  Viscosity, kinematic  52 mm²/s (40°C)   5,4 mm²/s (100°C) [ASTM D445]  Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)  Viscosity, kinematic  < 20,5 mm²/s (40 °C) - ASTM D7042  Aliphatic, alicyclic or aromatic hydrocarbon  Yes  Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)  Viscosity, kinematic  < 20,5 mm²/s (40 °C) - ASTM D7042	Viscosity, kinematic	< 20,5 mm²/s	
Viscosity, kinematic  52 mm²/s (40°C)   5,4 mm²/s (100°C) [ASTM D445]  Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)  Viscosity, kinematic  < 20,5 mm²/s (40 °C) - ASTM D7042  Aliphatic, alicyclic or aromatic hydrocarbon  Yes  Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)  Viscosity, kinematic  < 20,5 mm²/s (40 °C) - ASTM D7042	Aliphatic, alicyclic or aromatic hydrocarbon	Yes	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)         Viscosity, kinematic       < 20,5 mm²/s (40 °C) - ASTM D7042	C14-16-18 Alkyl phenol		
Viscosity, kinematic < 20,5 mm²/s (40 °C) - ASTM D7042  Aliphatic, alicyclic or aromatic hydrocarbon Yes  Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)  Viscosity, kinematic < 20,5 mm²/s (40 °C) - ASTM D7042	Viscosity, kinematic	52 mm²/s (40°C)   5,4 mm²/s (100°C) [ASTM D445]	
Aliphatic, alicyclic or aromatic hydrocarbon  Yes  Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)  Viscosity, kinematic  < 20,5 mm²/s (40 °C) - ASTM D7042	Lubricating oils (petroleum), C20-50, hydrotre	ated neutral oil-based (72623-87-1)	
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)  Viscosity, kinematic  < 20,5 mm²/s (40 °C) - ASTM D7042	Viscosity, kinematic	< 20,5 mm²/s (40 °C) - ASTM D7042	
Viscosity, kinematic < 20,5 mm²/s (40 °C) - ASTM D7042	Aliphatic, alicyclic or aromatic hydrocarbon	Yes	
· · · · · · · · · · · · · · · · · · ·	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)		
Aliphatic, alicyclic or aromatic hydrocarbon Yes	Viscosity, kinematic	< 20,5 mm²/s (40 °C) - ASTM D7042	
	Aliphatic, alicyclic or aromatic hydrocarbon	Yes	

#### 11.2. Information on other hazards

No additional information available

## **SECTION 12: Ecological information**

## 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse

effects in the environment.

Hazardous to the aquatic environment, short–term

(acute)

m : Not classified

: Not classified

Hazardous to the aquatic environment, long-term (chronic)

EN (English)

9/16

19-6-2024 (Revision date) 19-6-2024 (Printing date)

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Dec-1-ene, trimers, hydrogenated (157707-86-3)			
LC50 - Fish [1]	> 1000 mg/l		
EC50 - Crustacea [1]	> 1000 mg/l		
Distillates (petroleum), hydrotreated heavy pa	rraffinic (64742-54-7)		
LC50 - Fish [1]	> 100 mg/l (Pimephales promelas, 96h) (OECD 203 method)		
EC50 - Crustacea [1]	> 10000 mg/l (Gammarus pulex, 48h) (OECD 202 method)		
EC50 72h - Algae [1]	> 100 mg/l		
NOEC (acute)	≥ 100 mg/l (Pseudokirchnerella subcapitata, 72h) (OECD 201 method)		
NOEC chronic crustacea	10 mg/l (Daphnia magna, 21d) (OECD 211 method)		
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)]	bis(dithiophosphate) (93819-94-4)		
LC50 - Fish [1]	4,5 mg/l 96 h (Oncorhynchus mykiss) [OECD 203]		
EC50 - Crustacea [1]	5,4 mg/l Test organisms (species): Daphnia magna		
EC50 72h - Algae [1]	2,1 mg/l Test organisms (species): other:		
EC50 72h - Algae [2]	2 mg/l Test organisms (species): other:		
EC50 96h - Algae [1]	2,1 mg/l Test organisms (species): other:		
EC50 96h - Algae [2]	2 mg/l Test organisms (species): other:		
ErC50 algae	2,1 mg/l 96 h (Selenastrum capricornutum) [OECD 201]		
C14-16-18 Alkyl phenol			
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna		
Lubricating oils (petroleum), C20-50, hydrotre	ated neutral oil-based (72623-87-1)		
LC50 - Fish [1]	> 100 mg/l (Pimephales promelas, 96h) (OECD 203 method)		
LC50 - Other aquatic organisms [1]	> 10000 mg/l (Gammarus pulex, 48h) (OECD 202 method)		
NOEC (acute)	≥ 100 mg/l (Pseudokirchnerella subcapitata, 72h) (OECD 201 method)		
Lubricating oils (petroleum), C15-30, hydrotre	ated neutral oil-based (72623-86-0)		
LC50 - Fish [1]	> 100 mg/l		
EC50 - Crustacea [1]	> 10000 mg/l		
NOEC (acute)	≥ 100 mg/l (Pseudokirchnerella subcapitata, 72h) (OECD 211 method)		
NOEC chronic fish	> 1000 mg/l		
NOEC chronic crustacea	> 10 mg/l (Daphnia magna, 21d) (OECD 211 method)		
NOEC chronic algae	≥ 100 mg/l		
12.2 Parsistance and degradability			

## 12.2. Persistence and degradability

VatOil Syntruck Plus 5W-30		
Persistence and degradability Not rapidly degradable		
Dec-1-ene, trimers, hydrogenated (157707-86-3)		
Persistence and degradability  Not rapidly degradable		
Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)		
Persistence and degradability Potentially biodegradable.		

19-6-2024 (Revision date) 19-6-2024 (Printing date) EN (English) 10/16

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Distillates (petroleum), solvent-dewaxed heav	y paraffinic (64742-65-0)	
Persistence and degradability	Not rapidly degradable	
Paraffin oils (petroleum), catalytic dewaxed he	eavy (64742-70-7)	
Persistence and degradability	Not rapidly degradable	
Distillates (petroleum), hydrotreated heavy pa	raffinic (64742-54-7)	
Persistence and degradability	Not rapidly degradable	
Biodegradation	31 % (28d) (OECD 301F method)	
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)]	bis(dithiophosphate) (93819-94-4)	
Persistence and degradability	Not readily biodegradable.	
Biodegradation	1,5 % 28 d - 10mg/l [OECD 301 B]	
C14-16-18 Alkyl phenol		
Persistence and degradability	Not rapidly degradable	
Lubricating oils (petroleum), C20-50, hydrotre	ated neutral oil-based (72623-87-1)	
Persistence and degradability	Not rapidly degradable	
Biodegradation	31 % (28d) (OECD 301F method)	
Lubricating oils (petroleum), C15-30, hydrotre	ated neutral oil-based (72623-86-0)	
Persistence and degradability	Not readily biodegradable.	
Biodegradation	31 % (28d) (OECD 301F method)	
12.3. Bioaccumulative potential		
Dec-1-ene, trimers, hydrogenated (157707-86	-3)	
Partition coefficient n-octanol/water (Log Pow)	5 @20°C	
Distillates (petroleum), solvent-dewaxed light	paraffinic (64742-56-9)	
Partition coefficient n-octanol/water (Log Pow)	> 3	
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)]	bis(dithiophosphate) (93819-94-4)	
Partition coefficient n-octanol/water (Log Pow)	0,9 (23 °C)	
C14-16-18 Alkyl phenol		
Partition coefficient n-octanol/water (Log Pow)	> 7,2	
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)		
Partition coefficient n-octanol/water (Log Kow)	> 6	
Bioaccumulative potential	Bioaccumulative potential.	
12.4. Mobility in soil		
Distillates (petroleum), solvent-dewaxed light	paraffinic (64742-56-9)	
Ecology - soil	Insoluble in water.	
Lubricating oils (petroleum), C20-50, hydrotre	ated neutral oil-based (72623-87-1)	

9-6-2024 (Revision date) EN (English) 11/16

Product adsorbs onto the soil

Mobility in soil

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)	
Ecology - soil	Insoluble in water.

## 12.5. Results of PBT and vPvB assessment

Component	
Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9), zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate) (93819-94-4), Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1), Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)
Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9), zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate) (93819-94-4), Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1), Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)

## 12.6. Endocrine disrupting properties

No additional information available

#### 12.7. Other adverse effects

No additional information available

## **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

Regional waste regulation

Waste treatment methods

Sewage disposal recommendations

Product/Packaging disposal recommendations

Additional information

European List of Waste (LoW, EC 2000/532)

HP Code

- : Disposal must be done according to official regulations.
- : Do not allow into drains or water courses. Dispose of contents/container in accordance with

licensed collector's sorting instructions.

Disposal must be done according to official regulations.

- : Dispose in a safe manner in accordance with local/national regulations.
- : Do not re-use empty containers.
- : 13 02 05\* mineral-based non-chlorinated engine, gear and lubricating oils
- : HP4 "Irritant skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.

## **SECTION 14: Transport information**

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID	
14.1. UN number or ID n	14.1. UN number or ID number				
Not regulated for transport					
14.2. UN proper shippin	g name				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated	
14.3. Transport hazard o	14.3. Transport hazard class(es)				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated	
14.4. Packing group					
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated	
14.5. Environmental hazards					
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated	

19-6-2024 (Revision date) EN (English) 12/16

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
No supplementary information available				

## 14.6. Special precautions for user

#### **Overland transport**

Not regulated

## Transport by sea

Not regulated

## Air transport

Not regulated

## **Inland waterway transport**

Not regulated

#### Rail transport

Not regulated

## 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

## **REACH Annex XVII (Restriction List)**

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(b)	Dec-1-ene, trimers, hydrogenated; Distillates (petroleum), solvent-dewaxed light paraffinic; Distillates (petroleum), solvent-dewaxed heavy paraffinic; Paraffin oils (petroleum), catalytic dewaxed heavy; Distillates (petroleum), hydrotreated heavy paraffinic; zinc bis[O-(6-methylheptyl)] bis[O-(secbutyl)] bis(dithiophosphate); C14-16-18 Alkyl phenol; Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10

19-6-2024 (Revision date) 19-6-2024 (Printing date) 13/16 EN (English)

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(c)	zinc bis[O-(6- methylheptyl)] bis[O-(sec- butyl)] bis(dithiophosphate)	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1

#### **REACH Annex XIV (Authorisation List)**

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

#### **REACH Candidate List (SVHC)**

Contains no substance(s) listed on the REACH Candidate List

#### **PIC Regulation (Prior Informed Consent)**

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

#### **POP Regulation (Persistent Organic Pollutants)**

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

#### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

#### **Dual-Use Regulation (428/2009)**

Contains no substance subject to the COUNCIL REGULATION (EC) No 428/2009 of 5 May 2009 setting up a Community regime for the control of exports, transfer, brokering and transit of dual-use items.

#### VOC Directive (2004/42)

VOC content : 0 %

#### **Explosives Precursors Regulation (2019/1148)**

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

#### **Drug Precursors Regulation (273/2004)**

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

#### 15.1.2. National regulations

No additional information available

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

#### For the following substances of this mixture a chemical safety assessment has been carried out:

Distillates (petroleum), solvent-dewaxed light paraffinic

### **SECTION 16: Other information**

Indication of changes			
Section	Changed item	Change	Comments
	Supersedes	Modified	
	Revision date	Modified	
	Type of product	Added	
1.2	Function or use category	Removed	
2.1	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Removed	
4.1	First-aid measures general	Added	

19-6-2024 (Revision date) EN (English) 14/16

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Indication of changes			
Section	Changed item	Change	Comments
4.2	Symptoms/effects after skin contact	Added	
4.2	Symptoms/effects after inhalation	Added	
4.2	Symptoms/effects after ingestion	Added	
4.2	Symptoms/effects after eye contact	Added	
5.2	Explosion hazard	Added	
5.3	Firefighting instructions	Added	
6.1	Protective equipment	Added	
6.1	Emergency procedures	Added	
6.1	General measures	Added	
6.3	For containment	Added	
7.1	Additional hazards when processed	Added	
7.2	Technical measures	Added	
7.2	Packaging materials	Added	
8.2	Personal protective equipment	Added	
13.1	Sewage disposal recommendations	Added	
13.1	H code	Added	
13.1	Additional information	Added	
13.1	Regional waste regulation	Added	

Abbreviations and acronyms:		
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	Acute Toxicity Estimate	
BCF	Bioconcentration factor	
BLV	Biological limit value	
BOD	Biochemical oxygen demand (BOD)	
COD	Chemical oxygen demand (COD)	
DMEL	Derived Minimal Effect level	
DNEL	Derived-No Effect Level	
EC-No.	European Community number	
EC50	Median effective concentration	
EN	European Standard	
IARC	International Agency for Research on Cancer	
IATA	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	
LC50	Median lethal concentration	
LD50	Median lethal dose	
LOAEL	Lowest Observed Adverse Effect Level	

19-6-2024 (Revision date) 19-6-2024 (Printing date)

EN (English)

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
EUH208	Contains C14-16-18 Alkyl phenol. May produce an allergic reaction.
EUH210	Safety data sheet available on request.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1B	Skin sensitisation, category 1B
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.