

Product Information 09.40.02

21-10-2019

Drauliquid-S DOT 4

Description

Drauliquid-S DOT 4 is a synthetic brake fluid with the following properties:

- A very low pour point
- Does not affect seals
- Minimum signs of corrosion

Application

Drauliquid -S DOT 4 can be used in all hydraulically operated braking systems with both drum and disc brakes that require DOT 4 brake fluid.

Specifications

FMVSS 116 DOT 4

SAE J1703, ISO 4925

Typicals

Density at 15 °C, kg/l	1,030
Viscosity -40 °C, mm ² /s	1200
Viscosity 100 °C, mm ² /s	2,30
Flash Point PM, °C	91
Boiling Point (reflux) , °C	263
Wet Boiling Point, °C	168
pH - 50% in ethanolsolution	8,0

Available packagings



04006

250 ml bottle



35663

500 ml bottle



04206

1 L bottle



04304

5 L can



32975

20 L Bag in
Box



56152

20 L pail



14102

60 L drum



31364

208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.