

Product Information 09.40.02 26-04-2024

Kroon-Oil Drauliquid-S DOT 4

Description

Drauliquid-S DOT 4 is a synthetic brake fluid with the following properties:

- A very low pour point
- Does not affect seals
- Minimum signs of corrosion

Application

Drauliquid -S DOT 4 can be used in all hydraulically operated braking systems with both drum and disc brakes that require DOT 4 brake

Specifications

FMVSS 116 DOT 4

SAE J1703, ISO 4925

Typicals

Density at 15 °C, kg/l	1,062
Viscosity -40 °C, mm ² /s	1270
Viscosity 100 °C, mm ² /s	2,10
Flash Point PM, °C	91
Boiling Point (reflux) , °C	261
Wet Boiling Point, °C	158
pH - 50% in ethanolsolution	8.0

Available packagings

















20 L pail





04006 250 ml bottle

35663 500 ml bottle

04206 1 L bottle

04304 5 L can

15 L Bag in Box

20 L Bag in Box

60 L drum

31364 208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.