



## Product Information 01.50.11

21-02-2019

### Kroontrak Super 15W-30

#### Description

Kroontrak Super 15W-30 is a modern multifunctional oil for use in agricultural and earth-moving machinery. The product is based on premium solvent-refined base oils with additives to achieve the following properties:

- Powerful dispersion and detergency
- High resistance to wear, corrosion and foaming
- Very high resistance to oxidation
- Excellent EP properties
- A high and stable viscosity index

#### Application

Kroontrak Super 15W-30 has been specially developed for everyday operating conditions in agriculture. The universal, multifunctional oil is what is known as an STOU: Super Tractor Oil Universal. It is therefore suitable for use as an all-purpose lubricant for:

- Petrol engines
- Diesel engines and turbo diesels
- Transmissions, also for wet brakes
- Hydraulic systems

#### Specifications

API SF/CG-4/GL-4

ACEA E3, MIL-L-2104D

Ford M2C159-C

Massey Ferguson CMS M1139/M1144/M1145

MB 227.1

ZF TE-ML 06B/07B

Allison C4

Cat TO-2

Ford M2C134-D

John Deere J20C

Massey Ferguson CMS M1135/M1143

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

### Typicals

Density at 15 °C, kg/l	0,867
Viscosity -20 °C, mPa.s	6000
Viscosity 40 °C, mm <sup>2</sup> /s	76,60
Viscosity 100 °C, mm <sup>2</sup> /s	10,50
Viscosity Index	122
Flash Point COC, °C	220
Pour Point, °C	-36
Total Base Number, mgKOH/g	11,3
Sulphate Ash, %	1,57
Noack, %	12,0

### Available packagings



34222  
5 L can



35045  
20 L pail



10071  
20 L can



10127  
60 L drum



34749  
200 L drum



10227  
208 L drum



35188  
999 L IBC

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.